

Voice Cables APAC

- 25pr, 50pr, or 100pr
- Suitable for voice and low grade data
- Category 3 and Category 5 compliant

Voice grade cables are used to integrate telephony applications in the backbone of a LAN infrastructure. They are multipair twisted pair cables and exist in Category 3, Category 5 and Category 5e performance levels.



STANDARDS

ANSI/TIA-568-C.2

ISO/IEC 11801

Voice Cables APAC

EIGENSCHAFTEN

Konstruktionsmerkmale

Außenmantel	LSZH
Kabeltype	U/UTP










Abmessungsmerkmale



Anzahl Paare	25
--------------	----

Anwendungsmerkmale

Kategorie	Cat. 3
-----------	--------

Product list

Aginode ref.	Country ref.	Name	Außenmantel	Kabeltype	Anzahl Paare	Kategorie
 N100.817N-3	-	Voice U/UTP 25 pair AWG24 Cat 3 LSZH-FRT Orange reel	LSZH	U/UTP	25	Cat. 3
 N100.819N-3	-	Voice U/UTP 100 pair AWG24 Cat 3 LSZH-FRT Orange reel	LSZH	U/UTP	100	Cat. 3
 N100.818N	-	Voice U/UTP 50 pair AWG24 Cat 3 LSZH Orange reel	LSZH	U/UTP	50	Cat. 3
 N100.819N	-	Voice U/UTP 100 pair 24 AWG Cat 3 LSZH Orange Reel	LSZH	U/UTP	100	Cat. 3
 N100.M22	-	Voice U/UTP 25 pair AWG24 Cat 5e LSZH Orange 1000m reel	LSZH	U/UTP	25	Cat. 5e
 N100.817N	-	Voice U/UTP 25 pair AWG24 Cat 3 LSZH Orange reel	LSZH	U/UTP	25	Cat. 3
 N100.837N	-	Voice U/UTP 25 pair AWG24 Cat 3 PE 1000m reel	PE	U/UTP	25	Cat. 3
 N100.838N	-	Voice U/UTP 50 pair AWG24 Cat 3 PE 1000m reel	PE	U/UTP	50	Cat. 3
 N100.818N-3	-	Voice U/UTP 50 pair AWG24 Cat 3 LSZH-FRT Orange reel	LSZH	U/UTP	50	Cat. 3

 = Make to order,  = In Stock

All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Aginode is indicative only and shall not be binding on Aginode or be treated as constituting a representation on the part of Aginode.