XPLORER™

Aginode XPLORER™ is a series of innovative optical distribution frames modules developed to meet the future of optical fibre networks. With improved modularity and robustness, greater simplicity and lightness and symmetrical shape, XPLORER™ will push the limits of optical distribution frame solutions.



XPLORER™ is a range of premium injection molded optical modules. It allows several functions (combined or not): splicing, patching, splitting and storage. Five concepts influenced the design of the range: modularity, simplicity, robustness, lightness and symmetry.



Modularity

- Adapting our products to specific operators' usages.
- Anticipating upcoming evolutions of optical fibre networks.

Simplicity

- Designed for intuitive installation and usage.
- Standing free from installation hazards.

Robustness

- Working for a durable network performance.
- Ensuring optimal functionning over all life phases for all applications.

Lightness

- Taking security and penibility into account.
- Enhancing transport conditions.

Symmetry

- Allowing polyvalence of installations with low products diversity.
- Reducing stock management and order complexity.

Aginode XPLORER™ is an optimised universal solution of optical distribution frame modules for both small-scale and large-scale deployments.

STANDARDS

IEC 61753-1

All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Aginode is indicative only and shall not be binding on Aginode or be treated as constituting a representation on the part of Aginode.

XPLORER™

EIGENSCHAFTEN

Konstruktionsmerkmale	
Schaltschrankformat	19"
Farbe	Light grey RAL 7035
Werkstoff	Thermoplastic
Abmessungsmerkmale	
Durchmesser, Bereich	5...19 mm
Tiefe	185 mm
Einheitshöhe	1 U
Anwendungsmerkmale	
Chemische Beständigkeit	Hydrocarbons resistant
flammwidrig	UL94-V0
Funktion	Splicing and Patching
Mindestbiegeradius bei statischem Einsatz	30 mm
Betriebstemperatur	-40...75 °C
UV Beständigkeit	Ja

Resources

Dokumentation

XPLORER 1U installation manual - Splice and patch pdf — 5.69 MB Herunterladen

XPLORER 1U installation manual - Splitter pdf — 5.45 MB Herunterladen

XPLORER 1U installation manual - Patching pdf — 3.72 MB Herunterladen

XPLORER 1U installation manual - Storage pdf — 6.21 MB Herunterladen

XPLORER 3U installation manual - Splitter pdf — 6.86 MB Herunterladen

XPLORER 4U installation manual - Patching pdf — 15.49 MB Herunterladen

XPLORER 4U installation manual - Splice and patch pdf — 17.55 MB Herunterladen

XPLORER 4U installation manual - Splice and patch - 3 large splice cassettes pdf — 4.48 MB Herunterladen

XPLORER 1U installation manual - Splice, patch and splitter pdf — 7.1 MB Herunterladen

Eco-design at Aginode - FTTH case study pdf — 1.49 MB Herunterladen

All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Aginode is indicative only and shall not be binding on Aginode or be treated as constituting a representation on the part of Aginode.

Verkauf & Lieferung Informationen

Delivery units - 1U : 72 units per palet - 3U and 4U : 20 units per palet

All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Aginode is indicative only and shall not be binding on Aginode or be treated as constituting a representation on the part of Aginode.

Product list

	Aginode ref.	Country ref.	Name	Einheitshöhe	Funktion
	-	-	XPLORER™ - Splicing and patching 1U	1 (U)	Splicing and Patching
		-	XPLORER™ - Splicing and patching 4U	4 (U)	Splicing and Patching
		-	XPLORER™ - Splitting, Splicing and patching 3U	3 (U)	Splitting, Splicing and Patching
	10278809	-	XPLORER™ Back storage module	1 (U)	Storage
		-	XPLORER™ - Splitting, Splicing and patching 1U	1 (U)	Splitting, Splicing and Patching
	-	-	XPLORER™ - Patching 1U	1 (U)	Patching
		-	XPLORER™ - Patching 4U	4 (U)	Patching

= Make to order, = In Stock

All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Aginode is indicative only and shall not be binding on Aginode or be treated as constituting a representation on the part of Aginode.