

Optical Transition Box

- 316L stainless steel cabinet
- Designed for harsh and marine environments
- Optical module with combined splicing and patching functions integrated in the cabinet
- Specific IP66 devices for breakout and submarine cables

The Optical Transition Box allows to connect wind turbines together. Hybrid cables (power and fibre) are used and terminated in this box which is located at the base of the wind turbines. It is designed in 316L stainless steel material due to its installation in Wind Farm. Its protection degrees IP66 and IK10 are compatible for a use in harsh environment. The product allows to connect several breakout cables and submarine hybrid cables. It is equipped with a COSH optical module which combines splicing and patching functions (up to 96 LC/UPC adaptors and 192 splices).

The incoming submarine cables are spliced to pigtails, ready for splicing in cassettes, which are connected on the back of the patch panel. Incoming cables can be also spliced directly to the outgoing submarine cable going to another cabinet. Each cable entry for submarine cable is equipped with a BAEP fan-out and clamping device. The box has also cable entries compatible for 12OF breakout cables terminated with LC/UPC adapters which are plugged to the patch panel. The IP66 watertightness is guaranteed thanks to the specific ROXTEC cable glands and seals for breakout or hybrid cables. Individual grounding for submarine cables are available and linked to the grounding system of the cabinet ensuring a electrical continuity between all components.

The box is secured by 2 key locks and can be mounted easily thanks to its 4 fixing points outside the product.

The product is delivered in wood box (NIMP15) and fully equipped with adaptors and pigtails, mounted and tested, ready for termination.

Compliant with ISO 9001, ISO 14001 and OHSAS 18001.



Optical Transition Box

EIGENSCHAFTEN

Konstruktionsmerkmale

Farbe	grau
Boxtype	Splicing and patching
Werkstoff	Stainless Steel

Abmessungsmerkmale

Tiefe	300 mm
Höhe	600 mm
Gewicht	35000 g
Breite	600 mm
Max. Kassetten Anzahl	4
Anzahl Spleiße	192
Maximale Anzahl von Adaptern	96

Mechanische Eigenschaften

IK-Bewertung	10
--------------	----

Anwendungsmerkmale

Einsatzbereich	Uebergang
Adapter	LC/UPC
Mittenabstand	No
Verpackung	Box
Art der Installation	Outdoor
RoHS compliant	Yes
Watertightness	IP66
Minimaler Biegerradius - Installiert	30 mm

Resources

Dokumentation

All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Aginode is indicative only and shall not be binding on Aginode or be treated as constituting a representation on the part of Aginode.

Product list

	Aginode ref.	Country ref.	Name	Maximale Anzahl von Adaptern
☎	10283569	-	Optical Transition Box 96 - OTB 96	96
☎	10265597	-	Optical Transition Box 48 - OTB 48	48
	13200853	-	Optical Transition Box - OTB 192	2 x 96
☎ = Make to order, 🏠 = In Stock				

All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Aginode is indicative only and shall not be binding on Aginode or be treated as constituting a representation on the part of Aginode.