

LANmark-OF ENSPACE Method B MTP-MTP Pre-Term OFNP APAC

- Factory terminated MTP-MTP fibre assembly
- Flexible fan-out for ease of installation in patch panel
- Small cable diameter reduces required data centre space
- Method B polarity Pre-Term
- Optimized for 40G/100G parallel applications
- Fibre count: 12F, 24F, 48F, 96F and 144F
- Fibre type: OM3, OM4 and singlemode (OS2)

Fire performance

The cables have been tested for fire performance according to UL Plenum performance.

According to this standard the cables have a very high fire performance with minimal fire load and can be used in air flow space.

MTP*-MTP Pre-Term characteristics

The MTP-MTP Pre-Term has standard pinned (male) connectors. This matches with the un-pinned (female) connectors in the ENSPACE modules and the female Plug&Play modules.

After the cable gland the Pre-Term has a fan-out. The fan-out splits the cable into tubes. The tubes are reinforced with aramid yarns. At the end of each tube a MTP-connectors is mounted. The jacket of the tube is the same colour as the cable jacket. Close to the MTP-connector a label is installed to identify the number of the leg.

The Pre-Terms are optimized for both pulling and laying in data centers. On both sides the MTP connectors are protected by a bubble foam. The maximum pulling force on the pulling eye is 450N. The detachable pulling eye with corrugated tube can be ordered using PN N890.100HP.

The MTP-MTP Pre-Terms come with a PG-13 cable gland that fits into the LANmark-OF ENSPACE and Plug&Play patch panel slots.



STANDARDS

ISO/IEC 11801

Optical Performance and Polarity

The insertion loss for a multimode the MTP-MTP* connection has Low Loss performance: typical insertion loss is 0,25 dB with a maximum of 0,35 dB insertion loss.

The insertion loss for a singlemode the MTP-MTP* connection has Ultra Low Loss performance: typical insertion loss 0.25dB with a maximum of 0.35dB insertion loss.

The insertion loss of a MTP-MTP* connection is measured according to standard IEC61300-3-45.

The minimum return loss for a multimode MTP connection is 20 dB measured according to IEC 61300-3-6. The minimum return loss for a singlemode MTP connection is 45 dB measured according to IEC 61300-3-6.

The method B Pre-Term has a key up / key up design. This is in agreement with standard TIA-568.3-D-2016 method B.

LANmark-OF ENSPACE Method B MTP-MTP Pre-Term OFNP APAC

EIGENSCHAFTEN

Konstruktionsmerkmale

Fasertyp SM (G657.A1)

Abmessungsmerkmale

Anzahl der optischen Fasern 12

Außendurchmesser, nom. 4.5 mm

Mechanische Eigenschaften

Mechanische Festigkeit gegen Schläge 10 impacts of 3 N.m

Querdruckwiderstand (IEC 794-1-E3) 100 N/cm

Maximale Zugspannung bei Installation 450 N

Übertragungseigenschaften

Insertion Loss, maximum, dB 0.35 dB

Rückflusdämpfung, max. dB 45 dB

Anwendungsmerkmale

Betriebstemperatur -20...60 °C

Minimaler Biegeradius bewegt 20 (xD)

Biegeradius min. nach Verlegung (xD) 10

Product list

Aginode ref.	Country ref.	Name	Fasertyp	Außendurchmesser, nom.	Anzahl der optischen Fasern	Querdruckwiderstand (IEC 794-1-E3)	Maximale Zugspannung bei Installation	Mechanische Festigkeit gegen Schläge
☎ N144.O12MMExxxY	-	LANmark-OF ENSPACE Method B 12F x SM Ultra Low Loss MTP Male APC - MTP Male APC Pre-Term xxxm OFNP Yellow	SM (G657.A1)	4.5 (mm)	12	100 (N/cm)	450 (N)	10 impact 3 N.m
☎ N144.O24MMExxxY	-	LANmark-OF ENSPACE Method B 24F x SM Ultra Low Loss MTP Male APC - MTP Male APC Pre-Term xxxm OFNP Yellow	SM (G657.A1)	7.5 (mm)	24	100 (N/cm)	660 (N)	10 impact 3 N.m

All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Aginode is indicative only and shall not be binding on Aginode or be treated as constituting a representation on the part of Aginode.

Aginode ref.	Country ref.	Name	Fasertyp	Außendurchmesser, nom.	Anzahl der optischen Fasern	Querdruckwiderstand (IEC 794-1-E3)	Maximale Zugspannung bei Installation	Mechanische Festigkeit gegen Schläge
☎ N144.O48MMExxxY	-	LANmark-OF ENSPACE Method B 48F x SM Ultra Low Loss MTP Male APC - MTP Male APC Pre-Term xxxm OFNP Yellow	SM (G657.A1)	7.7 (mm)	48	100 (N/cm)	660 (N)	10 impact 3 N.m
☎ N144.O96MMExxxY	-	LANmark-OF ENSPACE Method B 96F x SM Ultra Low Loss MTP Male APC - MTP Male APC Pre-Term xxxm OFNP Yellow	SM (G657.A1)	10.0 (mm)	96	100 (N/cm)	1000 (N)	10 impact 3 N.m
☎ N145.O12MMExxxA	-	LANmark-OF ENSPACE Method B 12F x OM3 MTP Male - MTP Male Pre-Term xxxm OFNP Aqua	OM3 50/125	4.5 (mm)	12	100 (N/cm)	450 (N)	10 impact 3 N.m

All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Aginode is indicative only and shall not be binding on Aginode or be treated as constituting a representation on the part of Aginode.

Aginode ref.	Country ref.	Name	Fasertyp	Außendurchmesser, nom.	Anzahl der optischen Fasern	Querdruckwiderstand (IEC 794-1-E3)	Maximale Zugspannung bei Installation	Mechanische Festigkeit gegen Schläge
☎ N145.O24MMExxxA	-	LANmark-OF ENSPACE Method B 24F x OM3 MTP Male - MTP Male Pre-Term xxxm OFNP Aqua	OM3 50/125	7.5 (mm)	24	100 (N/cm)	660 (N)	10 impact 3 N.m
☎ N145.O48MMExxxA	-	LANmark-OF ENSPACE Method B 48F x OM3 MTP Male - MTP Male Pre-Term xxxm OFNP Aqua	OM3 50/125	7.7 (mm)	48	100 (N/cm)	660 (N)	10 impact 3 N.m
☎ N145.O96MMExxxA	-	LANmark-OF ENSPACE Method B 96F x OM3 MTP Male - MTP Male Pre-Term xxxm OFNP Aqua	OM3 50/125	10.0 (mm)	96	100 (N/cm)	1000 (N)	10 impact 3 N.m

All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Aginode is indicative only and shall not be binding on Aginode or be treated as constituting a representation on the part of Aginode.

Aginode ref.	Country ref.	Name	Fasertyp	Außendurchmesser, nom.	Anzahl der optischen Fasern	Querdruckwiderstand (IEC 794-1-E3)	Maximale Zugspannung bei Installation	Mechanische Festigkeit gegen Schläge
☎ N147.O12MMExxxA	-	LANmark-OF ENSPACE Method B 12F x OM4 MTP Male - MTP Male Pre-Term xxxm OFNP Aqua	OM4 50/125	4.5 (mm)	12	100 (N/cm)	450 (N)	10 impact 3 N.m
☎ N147.O24MMExxxA	-	LANmark-OF ENSPACE Method B 24F x OM4 MTP Male - MTP Male Pre-Term xxxm OFNP Aqua	OM4 50/125	7.5 (mm)	24	100 (N/cm)	660 (N)	10 impact 3 N.m
☎ N147.O48MMExxxA	-	LANmark-OF ENSPACE Method B 48F x OM4 MTP Male - MTP Male Pre-Term xxxm OFNP Aqua	OM4 50/125	7.7 (mm)	48	100 (N/cm)	660 (N)	10 impact 3 N.m

All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Aginode is indicative only and shall not be binding on Aginode or be treated as constituting a representation on the part of Aginode.

Aginode ref.	Country ref.	Name	Fasertyp	Außendurchmesser, nom.	Anzahl der optischen Fasern	Querdruckwiderstand (IEC 794-1-E3)	Maximale Zugspannung bei Installation	Mechanismen gegen Festigkeitsschläge
N147.O96MMExxxA	-	LANmark-OF ENSPACE Method B 96F x OM4 MTP Male - MTP Male Pre-Term xxxm OFNP Aqua	OM4 50/125	10.0 (mm)	96	100 (N/cm)	1000 (N)	10 impacts 3 N.m

All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Aginode is indicative only and shall not be binding on Aginode or be treated as constituting a representation on the part of Aginode.