LANmark-OF MPO-MPO-Verbindungskabel

- Das Aginode MPO-Patchkabel verfügt über ein schlankes Kabeldesign mit einem Außendurchmesser von 3 mm, wodurch Anwendern in Rechenzentren 19 % mehr Platz für das Kabelmanagement vor der Schalttafel zur Verfügung steht
- Die optische Leistung des Aginode-MPO-Steckers übertrifft den Branchenstandard und entspricht internationalen Normen.
- Erhältlich für Single-Mode und biegeunempfindliche OM3/OM4-Kabel
- Gerade Polarität (Typ B) gemäß TIA 568.C.3
- MPO-Buchsen an beiden Enden



STANDARDS

ANSI/TIA-568-C.3
ISO/IEC 11801

Anwendung

Aginode MPO-Patchkabel sind für Hochgeschwindigkeits-Netzwerkanwendungen in Rechenzentren wie 40G, 100G, 200G und 400G ausgelegt. Dank ihrer geringen Verluste unterstützen Aginode-Kabel mindestens 6 MPO-Verbindungen und ermöglichen so den Einsatz von Zwischenverteilern in großen Rechenzentren. Das MPO-Kabel ist für den Außendurchmesser (OD) optimiert und weist eine hohe Zugfestigkeit sowie eine gute Druckfestigkeit auf. Jeder MPO-Trunk wird werkseitig mit einem Prüfbericht ausgeliefert, um die Leistungsfähigkeit sicherzustellen.

- Die MPO-Stecker erfüllen die Normen IEC 61754-7-1 und GR-1435-CORE.
- Der MPO-Stecker für Multimode ist vom Typ PC, der MPO-Stecker für Singlemode vom Typ APC
- Das OF-Kabel entspricht den Normen IEC 60794
- Das Kabel besteht aus LSZH-Material und erfüllt die Normen IEC 60332-1, IEC 60332-3-24, IEC 61034-2 sowie IEC 60754-1 und 2
- Die Glasfaser entspricht den Normen IEC 60793-2-10 (A1a.2b OM3 und A1a.3b OM4) sowie IEC 60793-2-50 (B6_a1) und ITU-T G.657.A1 für Singlemode

All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Aginode is indicative only and shall not be binding on Aginode or be treated as constituting a representation on the part of Aginode.

LANmark-OF MPO-MPO-Verbindungskabel

EIGENSCHAFTEN

Konstruktionsmerkmale

Fasertyp	OM4 50/125

Übertragungseigenschaften

Insertion Loss, maximum, dB	0.25 dB

All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Aginode is indicative only and shall not be binding on Aginode or be treated as constituting a representation on the part of Aginode.

Product list

	Aginode ref.	Country ref.	Name
	N125.7SUV2	-	LANmark-OF MPO-MPO-Patchkabel, OM4, gerade, MPO-Buchse – MPO-Buchse, 12-adrig, LSZH, violett, extrem geringer Verlust, 2 m
	N125.7SLV2	-	LANmark-OF MPO-MPO patch cord, OM4, Straight, MPO Female-MPO female, 12core, LSZH, Aqua, Low loss, 2m
	N125.4SLY2	-	LANmark-OF MPO-MPO-Patchkabel, OS2 APC, G.657.A1, gerade, MPO-Buchse – MPO-Buchse, 12-adrig, LSZH, gelb, geringer Verlust, 2 m
	N125.5SLA2	-	LANmark-OF MPO-MPO-Patchkabel, OM3, gerade, MPO-Buchse – MPO-Buchse, 12-adrig, LSZH, Aqua, geringer Verlust, 2 m

= Make to order, = In Stock

All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Aginode is indicative only and shall not be binding on Aginode or be treated as constituting a representation on the part of Aginode.