

LANmark-OF Bow fibre cable 1-2C

- Most suitable for floor routing
- Smaller bending radius fiber
- Easy core take out with notch structure
- Fire retardant IEC 60332-1 & IEC60332-3C

Characteristics

Special low-bend-sensitivity fiber provides high bandwidth and excellent communication transmission property.

Singlemode G657A2 performance: compliant to IEC60793-2-10, subtype B6a.2

Novel flute design ,easily strip and splice ,simplify the installation maintenance.

Construction

Legend accompanying the cross section drawing:

1. Optical fibre
2. FRP
3. Outer sheath in LSZH material



STANDARDS

ANSI/TIA-568-C.3

IEC 60793-2-10

ISO/IEC 11801

LANmark-OF Bow fibre cable 1-2C

EIGENSCHAFTEN

Konstruktionsmerkmale

Farbe	Schwarz
Fasertyp	SM (G657.A2)

Abmessungsmerkmale

Höhe	2 mm
Gewicht	8 g
Breite	3 mm
Anzahl der optischen Fasern	2

Mechanische Eigenschaften

Mechanical resistance to impacts (IEC 60794-1-E4)	100 impacts of 1 N.m
Crush resistance (IEC 60794-1-E3)	1000 N/100mm
Max. Zugkraft (IEC 60794-1-2-E1)	80 N

Übertragungseigenschaften

Dämpfung, max. 1310 nm (verkabelt)	0.5 dB/1000m
Dämpfung, max 1550 MHz (verkabelt)	0.4 dB/1000m

Anwendungsmerkmale

Betriebstemperatur	-20...60 °C
Mindestbiegeradius bei statischem Einsatz	15 mm
Lagertemperatur, Bereich	-20...60 °C

Product list

	Aginode ref.	Country ref.	Name
☎	N174CH.002	-	FTTH Bow-type Drop Cable 2F LSZH,BLACK
☎	N174CH.001	-	FTTH Bow-type Drop Cable 1F LSZH,BLACK

☎ = Make to order, 🏠 = In Stock

All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Aginode is indicative only and shall not be binding on Aginode or be treated as constituting a representation on the part of Aginode.