WLB-Max : Indoor Wall Box

The WLB box range is designed to manage the infrastructure of passive solutions, ensuring efficient management of fibers and connections in network environments. It provides optimized cable organization, ensuring reliable and secure deployment.

Description

The WLB-Max is a compact and efficient fiber management solution designed for passive infrastructure cabling and other indoor fiber networks. It ensures secure connectivity, high-density fiber management, and easy maintenance.

Key Features

- Modular Design: Designed for easy integration in LAN environments.
- High-Capacity Termination: Supports up to up to 26 SC adapters.
- Secure Access: 8 mm triangular key locking system.
- Quick Installation & Maintenance: Tool-free door dismantling and front-access patching.
- Robust Build: Designed for reliable long-term indoor operation·

Applications

- Passive fiber optic infrastructure networks(GPON & P2P, FTTO...cet)
- Wall-mounted **fiber distribution point** for structured cabling

Disponible Version

- **Standard :** Comes with SC/APC adapters, ready for custom configurations.

STANDARDS

Aginode specification

WLB-Max : Indoor Wall Box

EIGENSCHAFTEN

Konstruktionsmerkmale	
Kabeleingang	From left
Farbe	Light grey RAL 7035
Werkstoff	Polycarbonate
Abmessungsmerkmale	
Tiefe	150 mm
Höhe	100 mm
Anzahl der Verbinder	26
Breite	450 m
Anwendungsmerkmale	
Adapter	SC/APC
Locking system	Triangle
Mindestbiegeradius bei statischem Einsatz	15 mm
Betriebstemperatur	-25...70 °C
Verpackung	Box

Product list

Aginode ref.	Country ref.	Name	Werkstoff	Anzahl der Verbinder
NWLB.X026DU.W	-	WLB-Max - Standard	Polycarbonate	26

= Make to order, = In Stock