

# LANmark-OF MG Universal LSZH

- Loose tube fibre cable, Multi-tube
- Rodent retardant thanks to a double layer glass yarn and yarn
- Outdoor installation in a duct
- Horizontal and vertical installation indoor
- Designed for splicing
- All fibres grades

## Description and Application

The loose tube design from Aginode provide a strong cable with high resistance to impacts.

Equipped with a central member, the cable can contains up to 144 fibres thanks to a multitube construction

The water swellable glass yarns and the water swellable tape makes this cable design watertight and suitable for installation outdoor in a duct by pulling. Its fire performance allows indoor installation as well.

## Characteristics

- Outdoor cable for installation in a duct and indoor cable
- Designed for termination by splicing
- Multitube design
- All dielectric
- Waterproof structure
- Rodent retardant
- UV-resistant
- Flame retardancy IEC 60332-1-2
- Available in all fibre grades
- Reaction to Fire Eca, according to EN50575:2014+A1:2016



## STANDARDS

ISO/IEC 11801

## Product list

Aginode ref.	Country ref.	Name
N164.MG96L1530B	-	LANmark-OF MG 96x Singlemode 9/125 OS2 LSZH Black
N165.MG96L1530B	-	LANmark-OF MG 96x Multimode 50/125 OM3 LSZH Black
N167.MG96L1530B	-	LANmark-OF MG 96x Multimode 50/125 OM4 LSZH Black

☎ = Make to order, 🏠 = In Stock

*All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Aginode is indicative only and shall not be binding on Aginode or be treated as constituting a representation on the part of Aginode.*