LANmark-OF UC PE (Einrohr-Stahlarmierung)

UC-Glasfaserkabel

- Im Außenbereich in Kabelkanälen oder direkt erdverlegt
- Gewellte Stahlbandarmierung
- Erhältlich in allen Faserqualitäten
- Bietet vollständigen Schutz vor Nagetieren





Beschreibung und Anwendung

die Konstruktion ist für die Verwendung im Freien in Kanälen und für die direkte Erdverlegung geeignet. Sie besteht aus einer gewellten Stahlbandarmierung, die vollständigen Nagetierschutz bietet. Sie ist von Glasfasern umgeben. Das Kabel hat einen Außenmantel aus HDPE.
Die Bündeladerkonstruktion hat eine Kapazität von bis zu 24 Fasern mit einem Durchmesser von 250 um. Der Abschluss der Fasern erfolgt durch Spleißen von Pigtails.
Das Kabel ist wasserdicht durch das Gel in der Bündelader und die wasserdichten Glasgarne.

Eigenschaften

- Kabel für den Außenbereich zur Verlegung in einem Kabelkanal oder zur direkten Erdverlegung
- Konzipiert für den Abschluss durch Spleißen
- Zentrale Bündeladerkonstruktion
- Schutz aus gewelltem Stahl
- Wasserdichte Struktur, nagetier- und UV-beständig
- Erhältlich in allen Faserqualitäten
- Erhältlich von 4-24 Fasern

STANDARDS

ISO/IEC 11801

All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Aginode is indicative only and shall not be binding on Aginode or be treated as constituting a representation on the part of Aginode.

LANmark-OF UC PE (Einrohr-Stahlarmierung)

EIGENSCHAFTEN

Konstruktionsmerkmale

Leitungsaufbau	Loose Tube
Fasertyp	SM (G657.A1)

All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Aginode is indicative only and shall not be binding on Aginode or be treated as constituting a representation on the part of Aginode.

Product list

Aginode ref.	Country ref.	Name
N164.UCPE06B	-	LANmark-OF UC 6x Singlemode 9/125 OS2 PE Black
N164.UCPE12B	-	LANmark-OF UC 12x Singlemode 9/125 OS2 PE Black
N164.UCPE24B	-	LANmark-OF UC 24x Singlemode 9/125 OS2 PE Black
N165.UCPE06B	-	LANmark-OF UC 6x Multimode 50/125 OM3 PE Black
N165.UCPE12B	-	LANmark-OF UC 12x Multimode 50/125 OM3 PE Black
N165.UCPE24B	-	LANmark-OF UC 24x Multimode 50/125 OM3 PE Black
N167.UCPE06B	-	LANmark-OF UC 6x Multimode 50/125 OM4 PE Black
N167.UCPE24B	-	LANmark-OF UC 24x Multimode 50/125 OM4 PE Black
N167.UCPE12B	-	LANmark-OF UC 12x Multimode 50/125 OM3 PE Black

= Make to order, = In Stock

All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Aginode is indicative only and shall not be binding on Aginode or be treated as constituting a representation on the part of Aginode.