

LANmark-OF Sliding Snap-In Patch Panels

- - Leere OF-Patchfelder mit Schiebemechanismus.
- - Geeignet für Direktanschluss oder Spleißen.
- - Innenverschiebung zur Berücksichtigung des Biegeradius des Patchkabels.
- - LANmark Aussehen

Kompatibilität

Geeignet für enge Buffer-Kabel (direkter Anschluss) , Loose Tube-Kabel mit Spleißkassette / Pigtailed-Anschlüsse.
Geeignet für vorkonfektionierte Anschlusskabel.

Einbau

- 19" Breite. 1U
- Bietet Platz für 24 ST oder 24 LANmark-OF Snap-Ins (oder 12DSC).
- 2 Positionen: bündig oder vertieft unter Berücksichtigung des Kabelbiegeradius.
- Wird mit Markierungsstreifen zur Nummerierung und Kategorisierung der Ports geliefert.



STANDARDS

ISO/IEC 11801

LANmark-OF Sliding Snap-In Patch Panels




EIGENSCHAFTEN



Abmessungsmerkmale

Tiefe	280 mm
Breite	19 inches
Einheitshöhe	1 U

All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Aginode is indicative only and shall not be binding on Aginode or be treated as constituting a representation on the part of Aginode.

Product list

	Aginode ref.	Country ref.	Name
	N439.4SNB-H	-	LANmark Hybrid Patch Panel Snap-In Sliding Black
	N439.4SNB	-	LANmark-OF Patch Panel Snap-In Sliding Black
	N439.4SNW	-	LANmark-OF Patch Panel Snap-In Sliding White

 = Make to order,  = In Stock

All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Aginode is indicative only and shall not be binding on Aginode or be treated as constituting a representation on the part of Aginode.