

Voice Cables APAC

VOICE U/UTP 100 PAIR 24 AWG CAT 3 LSZH ORANGE REEL

Aginode Ref: N100.819N

- Unshielded Cat 3 cable
- 100 pairs
- Suitable for voice and low grade data applications in LAN infrastructure
- LSZH outer sheath

Voice grade cables are used to integrate telephony applications in the backbone of a LAN infrastructure. They are multipair twisted pair cables and exist in Category 3, Category 5 and Category 5e performance levels.



STANDARDS

ANSI/TIA-568-C.2
ISO/IEC 11801

Voice U/UTP 100 pair 24 AWG Cat 3 LSZH Orange Reel

Eigenschaften

Konstruktionsmerkmale

Schirm	Nein
Außenmantel	LSZH
Mantelfarbe	Orange
Isolationsmaterial	PE
Kabeltype	U/UTP
Leitermaterial	Kupfer, blank

Abmessungsmerkmale

Anzahl Paare	100
Abmessung (AWG)	24
Außendurchmesser, nom.	22.5 mm

Elektrische Eigenschaften

Betriebskapazität	66 nF/km
Wellenwiderstand	100 Ohm

Mechanische Eigenschaften

Max. Zugkraft (IEC 60794-1-2-E1)	1200 N
----------------------------------	--------

Übertragungseigenschaften

Attenuation at 16 MHz	13.1 dB/100m
Dämpfung bei 1 MHz	2.6 dB/100m

Anwendungsmerkmale

Betriebstemperatur	-15...60 °C
Dynamischer Mindestbiegeradius während Anwendung	225.0 mm
Kategorie	Cat. 3
Flammwidrig	IEC 60332-1
Umgebungstemperatur bei Verlegung, Bereich	0...50 °C

All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Aginode is indicative only and shall not be binding on Aginode or be treated as constituting a representation on the part of Aginode.