

LANmark Industry IP65/67 Wanddosen

LANMARK INDUSTRY IP65/67 OUTLET KIT 2 SNAP-IN CATEGORY 7A BLACK

Aginode Ref: N42i.003

LANmark Industry IP67 Wanddosen

IP65/67 Wanddosen für LANs in der Industrie oder ungeschützter Umgebung.



STANDARDS

ISO/IEC 11801

ISO/IEC 24702

All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Aginode is indicative only and shall not be binding on Aginode or be treated as constituting a representation on the part of Aginode.

LANmark Industry IP65/67 outlet kit 2 Snap-In Category 7A black

Eigenschaften

Konstruktionsmerkmale

| | |
|--------------|---------------------|
| Farbe | Schwarz |
| Schirm | Ja |
| Kabeleingang | von oben oder unten |
| Werkstoff | Polycarbonate |
| Verbindertyp | RJ 45 |

Abmessungsmerkmale

| | |
|--------------------------|----------|
| Tiefe | 69 mm |
| Höhe | 173 mm |
| Anzahl der Schrauben | 4 |
| Breite | 90 mm |
| Abmessungen der Schraube | 4.00mm |
| Anzahl der Kabel | 2 |
| Wanddicke | 2.5 mm |
| Nettogewicht pro Stück | 0.29 kg |
| Länge festes Ende | 230.0 mm |

Elektrische Eigenschaften

| | |
|---------------------------|----------|
| Maximale Betriebsfrequenz | 1000 MHz |
| Wellenwiderstand | 100 Ohm |

Mechanische Eigenschaften

| | |
|--------------------------------------|----------------------------|
| Mechanische Festigkeit gegen Schläge | normale Industrieanwendung |
|--------------------------------------|----------------------------|


Anwendungsmerkmale

| | |
|-----------------------------|--------------------------|
| Elektromagnetisch geschirmt | Yes |
| Einsatzbereich | Industrial installations |
| Anzahl der Ports | 2 |
| Witterungsbeständig | Excellent |

All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Aginode is indicative only and shall not be binding on Aginode or be treated as constituting a representation on the part of Aginode.

| | |
|-------------------------|------------------------------------|
| Kategorie | Cat. 7A |
| Komponentenfunktion | Cabling and Connectivity solutions |
| Verpackung | Box |
| Max. Betriebstemperatur | 70 °C |
| Min. Betriebstemperatur | -40 °C |
| Wasserdicht | IP 65/67 |

Dokumentation

Freetable LM7A Channel.xls xls — 19 KB Herunterladen 

Verkauf & Lieferung Informationen

Includes automatic shutters, 2xCable Glands, 2xLANmark-7A shielded connector, 1xLabelling window. Colour: Black RAL9011