

120 System (4.75 inch)

FIBREROUTE 120MM(4.75 INCH) EQUAL TEE

Aginode Ref: N350.120FA02A

Aginode Fibre Trunking System provides a dedicated pathway for fibre optic cables and cords to protect them from accidental damage. The system offers a flexible, high-capacity solution for data centre containment which is easy to install and reconfigure to meet future needs.

- Pathway system designed for accommodation of data centre fibre cables
- Free of sharp edges
- Quick connect system with a wide range of fixtures and fittings
- High capacity pathway accommodating large volumes of cables with space for future expansion
- Equal Tee to provide branch connections in 120mm(4.75 inch) systems
- Tough, flame retardant ABS material

The Aginode Fibre Trunking System provides a dedicated pathway through data centre spaces and IT facilities for routing fibre cables.

The rigid channel with matching cover protects fibre optic cables from damage.

All components of the system are made of tough, fire retardant materials.

The system components have a smooth inner surface to ensure a safe path for fibre optic cables and feature internal radius management to facilitate the maintenance of bend radii for cables and patch cords.

The Equal Tee is used to create branches in 120mm(4.75 inch) channels. This form of interconnection is widely adopted in data centre designs compliant to ISO/IEC 11801-5, EN 50173-5 or EN 50600-2-4 within a ZD to create connections between rows.

All components of the system including the covers can be installed and uninstalled without special tools.

All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Aginode is indicative only and shall not be binding on Aginode or be treated as constituting a representation on the part of Aginode.



STANDARDS

EN 50173-5
ISO/IEC 24764
UL 94 V0

Size:

Depth 117mm(4.6")

Length 352mm(13.8")

Width 157mm(6.2")

FIBREROUTE 120mm(4.75 inch) Equal Tee

Eigenschaften

Konstruktionsmerkmale

Farbe	Gelb
Werkstoff	ABS

Abmessungsmerkmale

Tiefe	117 mm
Breite	157 mm
Länge	352 mm
Nettogewicht, ca.	0.6 kg

Anwendungsmerkmale

Betriebstemperatur	-25...60 °C
Lagertemperatur, Bereich	-45...60 °C