

# Railways - Multibundle K209B cables

MBC K209C LSZH 8X12SM G652D SP1757 BK

**Aginode Ref:** 10508458

Multi Micro-bundles cable with corrugated steel armour - 96 fibres

This multi micro-bundles cable is designed for indoor/outdoor installation in railways infrastructure.

The corrugated steel armour provides a high rodent protection. This cable has an outstanding fire behaviour.

Access to  $\mu$ bundles is made easy with the internal ripcord.

This cable can be operated under a large temperature range.

## Design

The MBC LSZH SP1757 cable has a central strength member (FRP : Fibre Reinforced Plastic), with 8 bundles around integrating 12 fibres each. The design is reinforced by a first layer of watertight glass, a LSZH\* inner sheath, a second layer of watertight glass yarns, a corrugated steel armour and a LSZH\* outer sheath.

## Fibre type



The MBC LSZH\* SP1757 cable is available with singlemode.

## Technical performances

The multibundle cable performances are specified in the following tables.

## Additional details

This cable is provided as a standard with a black sheath, other sheath colours are also available. Long exposure to UV with these other colours could generate colour fading.



## STANDARDS

EN 50399 B2  
IEC 60331-2  
IEC 60332-1  
IEC 60332-3  
IEC 60754-1  
IEC 60794  
IEC 61034  
NF C32-070/C1

All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Aginode is indicative only and shall not be binding on Aginode or be treated as constituting a representation on the part of Aginode.

## Euroclass

B2<sup>ca</sup> S1a a1 d0

\* LSZH: Low Smoke Zero Halogen.

# MBC K209c LSZH 8x12SM G652D SP1757 BK

## Eigenschaften

### Konstruktionsmerkmale

Farbe	Schwarz
Fasertyp	SM (G.652D)
Armierung	gewellter Stahl
Außenmantel	LSZH
Halogenfrei	IEC 60754-1
Verwendetes Material für Längswasserdichtigkeit	Quellfäden
Metallfrei	No
Zugentlastungselement	Central FRP
Leitungsaufbau	Multibundle
Additional strength member	Glass yarn

### Abmessungsmerkmale

Anzahl der Bündel	8
Nettogewicht ca.	230 kg/km
Anzahl der optischen Fasern	96
Außendurchmesser, nom.	13.7 mm

### Mechanische Eigenschaften

Mechanische Festigkeit gegen Schläge	10 impacts of 1 N.m
Maximalzulässige Dauerzuglast	2.65 kN
Querdruckwiderstand (IEC 794-1-E3)	300 N/cm
Maximale Zugspannung bei Installation	4000 N

### Übertragungseigenschaften

Dämpfung, max. 1310 nm (verkabelt)	0.36 dB/1000m
Dämpfung, max 1550 MHz (verkabelt)	0.23 dB/1000m

### Anwendungsmerkmale

Nagetierschutz	Corrugated steel tape
Betriebstemperatur	-20...60 °C
flammwidrig	IEC 60332-3

All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Aginode is indicative only and shall not be binding on Aginode or be treated as constituting a representation on the part of Aginode.

Mindestbiegeradius bei statischem Einsatz	270 mm
Flammwidrig	IEC 60332-1
Rauchdichte	IEC 61034-2
UV Beständigkeit	Good
Lagertemperatur, Bereich	-20...70 °C
Biegeradius während Verlegung	370 mm
Art der Installation	Indoor/Outdoor
Umgebungstemperatur, Bereich	-20...60 °C
Wasserdicht	Längs- und quer-

## Erklärung zur Leistung

MBC K209c LSZH 8x12SM G652D SP1757 BK pdf — 120.82 KB [Herunterladen](#) ↓

## Verkauf & Lieferung Informationen

## Standard Marking

Aginode - FIBRE OPTIC CABLE - MBC LSZH SP1400 - XXxYY - FB - TN - metric

XX = Fibre Count YY = Fibre Type FB = Frameries, Belgium (manufacturing place) TN = Traceability Number