

# Cat.6 450 F/UTP LSZH Dca

AGINODE C6 450 F/UTP LSZH DCA 4P 500M IVOIRY

**Aginode Ref:** 10269942

**EAN:** 3427630103593

- Complies to latest Cat 6 standard version
- Supports Class E applications
- Cable tested up to 450 MHz
- Flame retardant according to EN50575:2014+A1:2016 and IEC 60332-1
- Global screen for EMC performance
- Compatible POE, POE+ and UPOE
- RoHS EC Directive compliant
- Compliant with European Reach regulation
- N'Roll and MOBIWAY™ compatible

## Application



F/UTP Category 6 cables are the standard offering from Aginode. Manufactured in accordance with ISO IEC 61156-5 requirements, the F/UTP cable is the best choice to support all Class E applications like Ethernet, Fast Ethernet, Gigabit Ethernet, ... Cat 6 F/UTP cables are suitable for basic voice and data installations up to 250 MHz. Aginode Cat.6 cables, combined with a similar class of performance connectivity, are suitable for voice and data installations according to ISO/IEC 11801, EN 50173 and TIA/EIA 568 standards.

## Construction

1. Conductor: solid bare copper
2. Insulation : Polyethylen (EN 50290-2-23) - Two insulated conductors twisted to a pair
3. Cross filler - 4/2 laid up together
4. Tinned copper drain wire
5. Screen: ALU/PET foil - Alu inside
6. Outer Jacket : LSZH - Dca

## Environment

Designed to reduce the environment impact, Aginode cables are compliant with RoHS 2011/65 Directive and European Reach 1907/2006/EC regulation. The outer sheath of the cable is made of halogen free material (IEC 60754-1 / EN 50267-2-1),



## STANDARDS

EN 50173  
EN 50288  
EN 50575  
IEC 60332-1  
IEC 61156-5  
ISO/IEC 11801

All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Aginode is indicative only and shall not be binding on Aginode or be treated as constituting a representation on the part of Aginode.

with limited fumes emission (IEC 61034-1/2 / EN 50268-1/2) and no acid gas emission in case of fire (IEC 60754-2 / EN 50267-2-2).

Aginode measure the environmental impact of each of the cable. Upon request the PEP Ecopassport or the Eco Material Declaration could be available.

## Cat 6 450 F-UTP TRANSMISSION CHARACTERISTICS

CAT.6 450 F/UTP TRANSMISSION CHARACTERISTICS

Values at 20°C

Frequency (MHz)	S/T	4	10	16	20	100	200	250	350	450
Attenuation max. (dB/100m)	Standard	3.8	6.0	7.6	8.5	19.9	29.1	33.0	-	-
	Typical	3.6	5.5	6.9	7.7	17.6	25.4	28.6	34.4	39.5
NEXT min. (dB)	Standard	66.3	60.3	57.2	55.8	45.3	40.8	39.3	-	-
	Typical	80.5	72.7	68.8	66.9	53.3	47.4	45.5	42.7	40.5
PSNEXT min. (dB)	Standard	63.3	57.3	54.2	52.8	42.3	37.8	36.3	-	-
	Typical	77.5	69.7	65.8	63.9	50.3	44.4	42.5	39.7	37.5
ACRF min. (dB)	Standard	56.0	48.0	43.9	42.0	28.0	22.0	20.0	-	-
	Typical	85.5	76.3	71.5	69.3	53.1	46.1	43.9	40.5	38.0
PSACRF min. (dB)	Standard	53.0	45.0	40.9	39.0	25.0	19.0	17.0	-	-
	Typical	82.5	73.3	68.5	66.3	50.1	43.1	40.9	37.5	35.0
Return Loss min. (dB)	Standard	23.0	25.0	25.0	25.0	20.1	18.0	17.3	-	-
	Typical	27.0	29.0	29.0	29.0	24.5	22.5	21.9	20.9	20.2

All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Aginode is indicative only and shall not be binding on Aginode or be treated as constituting a representation on the part of Aginode.

# AGINODE C6 450 F/UTP LSZH Dca 4P 500m IVOIRY

## Eigenschaften

### Konstruktionsmerkmale

Außenmantel	LSZH
Mantelfarbe	Ivory
Halogenfrei	Ja
Higher heating value	821 MJ/km
Kabeltype	F/UTP
Gemeinsamer Schirm	Aluminium/polyester tape

### Abmessungsmerkmale

Nettogewicht ca.	49 kg/km
Anzahl Paare	4
Abmessung (AWG)	24
Durchmesser über Isolierung	1.13 mm
Außendurchmesser, nom.	7.1 mm
Außenabmessungen	Not applicable

### Elektrische Eigenschaften

Betriebskapazität	50 nF/km
Max. Gleichstromwiderstand des Leiters bei 20° C	95 Ohm/km
Characteristic impedance at 100 MHz	100 Ohm

### Mechanische Eigenschaften

Maximale Zugspannung bei Installation	80 N
---------------------------------------	------

### Übertragungseigenschaften

Ausbreitungsgeschwindigkeit	70 %
Kopplungsdämpfung bei 30 MHz	>50dB

### Anwendungsmerkmale

Einsatzbereich	Fixed installations
Kategorie	Cat. 6
Flammwidrig	IEC 60332-1
Rauchdichte	Ja

All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Aginode is indicative only and shall not be binding on Aginode or be treated as constituting a representation on the part of Aginode.

Verpackung	Trommel 500m
Umgebungstemperatur bei Verlegung, Bereich	0...50 °C
Biegefaktor bei Verlegung	8 (xD)
Biegefaktor nach Verlegung	4 (xD)
Temperaturbereich bei fester Verlegung	-20...70 °C

## Erklärung zur Leistung

AGINODE C6 450 F/UTP LSZH Dca 4P 500m IVOIRY pdf — 117.63 KB [Herunterladen](#) ↓