Outlets: @XS-Slim

@XS-SLIM KIT - INDOOR CABLE 1FO (PULLING)



Aginode Ref: 10272957

- **1 SC adapters**
- Wall mounted, on flush box or DIN rail
- No lid-opening to fix the outlet
- **Ready-to-fix** kit in option
- **1 Keystone slot** for RJ45 or coaxial plug delivered within the Hybrid optional kit

Optical terminal outlets, installed in the subscriber's home, are the optical equipments materializing the demarcation between the FTTH operator network and the local subscriber's network.

Compact and ergonomic, its design has been studied in **partnership with SismoDesign agency** for a sober, discreet and elegant depiction, to fit at best at the inhabitant.

For security, adapters include an **automatic laser and dust protection**, called « internal shutter ».

The front side contains all the necessary indications (from top to bottom):

- Swiveling flap to protect and hide the identification label
- Area to stick Identification Label (under the flap)
- Indication that polarizing slot is upwards
- Integrated laser symbol

The @XS-Slim outlets range comes in 2 families:

- The "equipped" outlet is provided with adapter and pigtail preinstalled. It must then be connected with the subscriber's cable.
- The "kit" outlet is provided pre-cabled, ready to be fastened without any outlet opening. Cable type and length are customizable.

STANDARDS

Aginode specification
Orange/France Telecom

All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Aginode is indicative only and shall not be binding on Aginode or be treated as constituting a representation on the part of Aginode.

@XS-Slim Kit - Indoor cable 1FO (pulling)

Eigenschaften

Konstruktionsmerkmale	
Werkstoff	Thermoplastic
Farbe	White RAL 9010
Abmessungsmerkmale	
Breite	80 mm
Anzahl Spleiße	2
Maximale Anzahl von Adaptern	1
Tiefe	25 mm
Durchmesser, Bereich	2...5 mm
Kabellänge	30 m
Höhe	80 mm
Mechanische Eigenschaften	
IK-Bewertung	5
Anwendungsmerkmale	
Verpackung	Box
UV Beständigkeit	Ja
Betriebstemperatur	-5...45 °C
Mindestbiegeradius bei statischem Einsatz	11 mm
Feuerbeständig	UL 94 V0
Adapter	SC/APC
Watertightness	IP 50

Dokumentation

Installation @XS-Hybrid/Slim pdf — 2.53 MB Herunterladen

ESERV_PTOCablesStd_EN_1.xlsx xlsx — 10.27 KB Herunterladen

@XS-FAST pdf — 981.89 KB Herunterladen

All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Aginode is indicative only and shall not be binding on Aginode or be treated as constituting a representation on the part of Aginode.