LWL Außenkabel mit zentraler Bündelader

UNITUBE CABLE 1X24SM SP1647



This unitube cable is used in the Access, Distribution, City Network and FTTx applications; it is designed to be easily installed in outdoor installations.

Characteristics & Applications

- Easy installation due to the friction properties of the outer sheath
- Robust design
- Waterproof structure
- Halogen free

Fibre type

The cable is available with different fibre types.

Construction

- Jelly filled tube
- Reinforcement elements
- Low friction outer sheath

STANDARDS

IEC 60794

All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Aginode is indicative only and shall not be binding on Aginode or be treated as constituting a representation on the part of Aginode.

Unitube Cable 1x24SM SP1647

Eigenschaften

Konstruktionsmerkmale	
Farbe	Schwarz
Fasertyp	SM
Armierung	Glasgarn
Außenmantel	PE HD
Leitungsaufbau	Unitube
dielektrisch	Yes
Abmessungsmerkmale	
Anzahl der Bündel	1
Nettogewicht ca.	40 kg/km
Anzahl der optischen Fasern	24
Außendurchmesser, nom.	6.9 mm
Mechanische Eigenschaften	
Zulässige Zugbelastbarkeit	180 daN
Anwendungsmerkmale	
Betriebstemperatur	-30...70 °C
Lagertemperatur, Bereich	-40...70 °C
Art der Installation	Rohranlagen
Umgebungstemperatur, Bereich	0...40 °C
Biegefaktor bei Verlegung	20 (xD)

All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Aginode is indicative only and shall not be binding on Aginode or be treated as constituting a representation on the part of Aginode.