Essential-6 U/UTP Cable

ESSENTIAL-6 U/UTP AWG24 CAT 6 LSZH ECA ORANGE 305M BOX

Aginode Ref: N100.161-OE

- Unshielded construction
- Complies to latest Category 6 standards
- Central cross maintains geometry and performance
- Supports Class E applications up to 250 MHz.



STANDARDS

ANSI/TIA-568-C.2
ISO/IEC 11801

Application

The Aginode Essential-6 cables are manufactured and tested to the latest Category 6 specifications. They are compatible with the complete Essential-6 modular and PCB connectivity range. When the cable is installed in conjunction with Essential-6 outlets and patch panels, a 25 year Class E Link Certificate can be obtained from the Aginode website.

Design

The Essential-6 cables have 24 AWG solid copper wires and comply with IEC 60228. The PE central cross filler keeps the pairs in place and reduces the risks of losing performance when bending the cable.
The cables are available with a Light Grey PVC or an Orange LSZH outer jacket.

Performance

Aginode Essential-6 cables are compliant with the requirements of the International, European and American cable standards, including ISO/IEC 11801, IEC 61156-5, EN 50173, EN 50288 and TIA/EIA 568-C.2.

Installation

The Essential-6 cables are as easy to install as their Category 5e equivalent, due to their small nominal outer diameter.

To support the correct set-up of hand held analysers for installation testing, the actual cable NVP value is given in the cable's print legend.

All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Aginode is indicative only and shall not be binding on Aginode or be treated as constituting a representation on the part of Aginode.

Essential-6 U/UTP AWG24 Cat 6 LSZH Eca Orange 305m box

Eigenschaften

Konstruktionsmerkmale	
Farbe	Orange
Außenmantel	LSZH
Kabeltype	U/UTP
Abmessungsmerkmale	
Nettogewicht ca.	35 kg/km
Abmessung (AWG)	24
Durchmesser über Isolierung	0.94 mm
Außendurchmesser, nom.	5.7 mm
Elektrische Eigenschaften	
Wellenwiderstand	100 Ohm
Übertragungseigenschaften	
Laufzeitdifferenz	30 ns/100m
Nebensprechdämpfung, 250 MHz	5.5 dB/100m
Ausbreitungsgeschwingigkeit	69 %
Phasenlaufzeit, max. 100 MHz	536 ns/100m
Anwendungsmerkmale	
Bereich	essential-6
Einsatzbereich	Innenraum
Betriebstemperatur	-20...60 °C
Kategorie	Cat. 6
Flammwidrig	IEC 60332-1
Rauchdichte	IEC 61034
Verpackung	Box 305 m
Umgebungstemperatur bei Verlegung, Bereich	-10...60 °C
Minimaler Biegeradius - Während der Installation (unter Spannung)	46 mm
Minimaler Biegerradius - Installiert	23 mm

All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Aginode is indicative only and shall not be binding on Aginode or be treated as constituting a representation on the part of Aginode.

Dokumentation

DoP EN N100161-OE pdf — 186.08 KB Herunterladen

Freetable Ess6 channel.xls xls — 14 KB Herunterladen

Erklärung zur Leistung

Essential-6 U/UTP AWG24 Cat 6 LSZH Eca Orange 305m box pdf — 141.6 KB Herunterladen

All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Aginode is indicative only and shall not be binding on Aginode or be treated as constituting a representation on the part of Aginode.