

# Essential-6 Cable

ESSENTIAL-6 U/UTP CAT 6 PVC 23AWG 305M REEL IN BOX

**Aginode Ref:** N100.175

- Unshielded construction
- Complies to latest Category 6 standards
- Central cross maintains geometry and performance
- Supports Class E applications up to 250 MHz.

## Application

The Aginode Essential-6 cables are manufactured and tested to the latest Category 6 specifications. They are compatible with the complete Essential-6 modular and PCB connectivity range. When the cable is installed in conjunction with Essential-6 outlets and patch panels, a 25 year Class E Link Certificate can be obtained from the Aginode website.

## Performance

Aginode Essential-6 cables are compliant with the requirements of the International, European and American cable standards, including ISO/IEC 11801, IEC 61156-5, EN 50173, EN 50288 and TIA/EIA 568-C.2.

## Installation

To support the correct set-up of hand held analysers for installation testing, the actual cable NVP value is given in the cable's print legend.

**Values given for 2-connector channel, built with Essential-6 cable, outlet and patch panel. (Values specified at 20°C)**



## STANDARDS

ANSI/TIA-568-C.2  
IEC 61156-5  
ISO/IEC 11801-1

# Essential-6 U/UTP Cat 6 PVC 23AWG 305m reel in box

## Eigenschaften

### Konstruktionsmerkmale

Farbe	grau
Außenmantel	PVC
Kabeltype	U/UTP

### Abmessungsmerkmale

Abmessung (AWG)	23
Durchmesser über Isolierung	1.0 mm
Außendurchmesser, nom.	6.1 mm

### Elektrische Eigenschaften

Betriebskapazität	56 nF/km
Wellenwiderstand	100 Ohm
Max. DC resistance of the conductor at 20°C (Ohm/km)	93.8

### Mechanische Eigenschaften

Max. Betriebszugkraft	10 N
-----------------------	------

### Übertragungseigenschaften

Laufzeitdifferenz	45 ns/100m
Phasenlaufzeit, max. 100 MHz	536 ns/100m

### Anwendungsmerkmale

Bereich	essential-6
Einsatzbereich	Innenraum
Länge	305 m
Betriebstemperatur	-20...60 °C
Kategorie	Cat. 6
Flammwidrig	IEC 60332-1
Rauchdichte	Nein
Verpackung	Reel in a box
Umgebungstemperatur bei Verlegung, Bereich	-10...60 °C

All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Aginode is indicative only and shall not be binding on Aginode or be treated as constituting a representation on the part of Aginode.

Minimaler Biegeradius - Während der Installation (unter Spannung)

49 mm

Minimaler Biegerradius - Installiert

25 mm

## Dokumentation

Freetable Ess6 channel.xls xls — 14 KB [Herunterladen](#) ⬇