

# LANmark-OF TB LSZH 2-24C - APAC Region

## LANMARK-OF TIGHT BUFFER LSZH OM4 24C AQUA

**Aginode Ref:** N177.031

Tight buffered optical fibre cables

- Indoor cable designed for backbone/horizontal installation
- All fibre grades
- Low Smoke Zero Halogene (LSZH)

### Description and Application

Aginode LANmark-OF TB Indoor fibre cable is designed for indoor applications. The fibre cable has 900µm tight buffered fibres with flame sheath around the transmission medium, and the 900µm sheath provides additional protection for the fibres. The cable is coated with aramid yarns as the strength member, and the outermost layer is coated with LSZH jacket. Bend Insensitive OM3/OM4 and SingleMode G.652.D and G.657.A1 are available.


The fibre cable is of a dry structure suitable for horizontal or vertical installation. The fibre cable meets the needs of indoor fire protection and can be installed in ducts.

- Can be installed both vertically or horizontally
- Applicable as standard multimode and singlemode fibre
- LSZH Jacket
- Tight buffered fibre for easy stripping

### Construction

Legend accompanying the cross section drawing for 2-24core OF cable:

1. 900µm Tight buffered fibre
2. Aramid yarn
3. LSZH jacket materials



### STANDARDS

- ANSI/TIA-568-C.3
- IEC 60332-1
- IEC 60332-3-24 Cat.C
- IEC 60793-2-10
- ISO/IEC 11801

# LANmark-OF Tight Buffer LSZH OM4 24C AQUA

## Eigenschaften

### Konstruktionsmerkmale

Farbe	Aqua
Fasertyp	OM4 50/125

### Abmessungsmerkmale

Aussendurchmesser	8.1 mm
Anzahl der optischen Fasern	24

### Mechanische Eigenschaften

Mechanical resistance to impacts (IEC 60794-1-E4)	100 impacts of 1 N.m
Crush resistance (IEC 60794-1-E3)	1000 N/100mm
Max. Zugkraft (IEC 60794-1-2-E1)	1300 N

### Anwendungsmerkmale

Betriebstemperatur	-20...60 °C
Dynamischer Mindestbiegeradius während Anwendung	162.0 mm
Mindestbiegeradius bei statischem Einsatz	81 mm
Lagertemperatur, Bereich	-30...70 °C
Umgebungstemperatur, Bereich	0...40 °C