

# LANmark-OF UC Outdoor PE 2-24core APAC Region

## LANMARK-OF UC PE 6CORE OM3 BLACK APAC REGION

**Aginode Ref:** N175.182

Suitable for in ducts or direct burial

- Corrugated steel tape armour
- Gel filled tube
- Available to multimode and singlemode fibre
- Provides rodent protection
- Outer Jacket is HDPE

### Description and Application

Aginode LANmark-OF UC fibre cable is designed for outdoor applications. The construction is suitable for use outdoor for direct burial. It consists of a Unitube structure protected by corrugated steel tape armouring, the Unitube can hold up to 24C fibres. This provides rodent protection and high crush resistance. The cable has a HDPE outer jacket.

### Construction

Legend accompanying the cross section drawing:

1. Optical fibres (250 um)
2. Waterproof gel filling
3. Loose tube
4. Glass Yarn
5. Corrugated steel tape armour
6. HDPE outer jacket with UV resistant additive

### Characteristics

- Designed for termination by splicing
- Central loose tube design
- Corrugated steel protection
- Waterproof structure and UV-resistant
- Available in Multimode and Singlemode fibre
- Available from 2-24 fibres



### STANDARDS

ANSI/TIA-568-C.3  
IEC 60793-2-10  
ISO/IEC 11801

# LANmark-OF UC PE 6core OM3 Black APAC Region

## Eigenschaften

### Konstruktionsmerkmale

Fasertyp	OM3 50/125
Armierung	verzinkte Stahlbaender
Außenmantel	PE HD
Mantelfarbe	Schwarz

### Abmessungsmerkmale

Aussendurchmesser	8.2 mm
Anzahl der optischen Fasern	6

### Mechanische Eigenschaften

Mechanical resistance to impacts (IEC 60794-1-E4)	100 impacts of 1 N.m
Max. Zugkraft (IEC 60794-1-2-E1)	1300 N
Querdruckwiderstand (IEC 794-1-E3)	300 N/cm

### Anwendungsmerkmale

Betriebstemperatur	-20...60 °C
Dynamischer Mindestbiegeradius während Anwendung	164.0 mm
Mindestbiegeradius bei statischem Einsatz	82 mm
Lagertemperatur, Bereich	-30...60 °C
Umgebungstemperatur bei Verlegung, Bereich	0...40 °C