# Power To The Antenna D-CORE - Dca (N2XC2Y)


**POWER TO THE ANTENNA D-CORE - DCA 25MM²**

Power To The Antenna D-CORE is a shielded dual conductor power cable. It can be used as a DC power cable for the interconnexion between Base Unit and Radio Units on mobile towers or rooftops. The D-shape of the isolated conductors enables to reduce the diameter and weight of these cables with no negative impact on the properties. It also has best-in-class flexibility. The Dca fire euroclass allows indoor usage when needed.




### Applications

- DC power cable 0.6/1.0 kV
- For indoor/outdoor applications
- Used on mobile phone towers or rooftops




### Cable construction

1. Stranded Bare copper
2. Insulation (IEC 60811-1) XLPE - Blue/Brown or White/Red
3. Longitudinal aluminium tape
4. Tinned copper braid (Coverage US >65%)
5. Outer sheath: HFFR - Black - Dca (EN50575)

### Environment

Designed to reduce the environment impact, Aginode cables are compliant with RoHS 2011/65 Directive and European Reach 1907/2006/EC regulation.

## D-CORE Picture



## STANDARDS

EN 50575
IEC 60228
IEC 60332-1
IEC 60502-1

*All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Aginode is indicative only and shall not be binding on Aginode or be treated as constituting a representation on the part of Aginode.*

# Power To The Antenna D-CORE - Dca 25mm²

## Eigenschaften

| | |
|---|---|
| **Konstruktionsmerkmale** | |
| Schirm | Aluminium-Polyester tape + tinned copper braid |
| Außenmantel | LSZH |
| Mantelfarbe | Schwarz |
| Aderfarbe | Blue - Brown |
| Leitermaterial | Bare copper class 5 |
| Isolierung | VPE |
| **Abmessungsmerkmale** | |
| Nettogewicht ca. | 710 kg/km |
| Aussendurchmesser | 17 mm |
| Aderanzahl | 2 |
| Leiterquerschnitt | 25 mm² |
| Durchmesser über Isolierung, Bereich | 10.4...10.6 mm |
| **Elektrische Eigenschaften** | |
| Max. Gleichstromwiderstand des Leiters bei 20° C | 0.78 Ohm/km |
| Minimaler Isolationswiderstand | 10 MOhm.km |
| Breakdown voltage Vcc, 5 min. | 3500.0 V |
| **Anwendungsmerkmale** | |
| RoHS conform | RoHS 2011/65/EU |
| Korrosivität der (Brand-)Gase | IEC 60754-1; IEC 60754-2 |
| Betriebstemperatur | -40...90 °C |
| Flammwidrig | IEC 60332-1 |
| Rauchdichte | Ja |
| UV Beständigkeit | Ja |
| Verpackung | Trommel 500m |
| Lagertemperatur, Bereich | -40...50 °C |
| Biegefaktor bei Verlegung | 8 (xD) |
| Biegefaktor nach Verlegung | 4 (xD) |

*All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Aginode is indicative only and shall not be binding on Aginode or be treated as constituting a representation on the part of Aginode.*

## Dokumentation

Leaflet 4G and 5G_En_v2_1_1.pdf pdf — 7.02 MB  Herunterladen

*All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Aginode is indicative only and shall not be binding on Aginode or be treated as constituting a representation on the part of Aginode.*