Gigabit SFP Transceiver

AGINODE SFP 1000 TRANSCEIVER SM(LC)E L10



Aginode Ref: 88646016

Aginode Small Form Factor Pluggable (SFP) Transceiver sind für den Einsatz in LANactive Switchen konzipiert. Aginode SFPs unterstützen verschiedene Wellenlängen und sind für unterschiedliche Entfernungen und verschiedene Anwendungen optimiert. Alle Aginode SFPs unterstützen Digital Diagnostic Monitoring (DDM) und sind SFP MSA (Multi-Source Agreement) und SFF-8472 konform. Alle SFPs erfüllen die Lasersicherheitsanforderungen der Klasse I gemäß IEC-825.

Gigabit Singlemode SFP

- Ethernet Standard: 1000Base-LX
- Glasfaser: Singlemode
- Wellenlänge: Tx/Rx 1310nm
- Distanz: 10km
- Duplex Verbindung
- Class 1 Laser Safety Compliance
- Wide operating temperature range, -40 to +85°C

Dokumentation

Detailed datasheet pdf — 243.38 KB Herunterladen

All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Aginode is indicative only and shall not be binding on Aginode or be treated as constituting a representation on the part of Aginode.