

# AGINODE PTTA D-CORE - Eca

AGINODE D-CORE 2X6 BA+RG LSZH ECA 500M

**Aginode Ref:** 13200080

**EAN:** 3427630107836

Power To The Antenna D-CORE is a shielded dual conductor power cable. It can be used as a DC power cable for the interconnexion between Base Unit and Radio Units on mobile towers or rooftops. The D-shape of the isolated conductors enables to reduce the diameter and weight of these cables with no negative impact on the properties. It also has best-in-class flexibility.

## Applications

- Power cable 0.6/1.0 kV
- For indoor/outdoor applications
- Used on mobile phone masts

## Cable construction

1. **Bare conductor strand - Class 5**
2. **Insulation (IEC 60811-1)XLPE**
3. **Longitudinal ALU/PET tape**
4. **Tinned copper braid (Coverage US >65%)**
5. **Outer sheath: Eca**  
HFFR - Black

## Environment

Designed to reduce the environment impact, Aginode cables are compliant with RoHS 2011/65 Directive and European Reach 1907/2006/EC regulation.

## D-CORE Picture



## STANDARDS

IEC 60332-1

IEC 60502-1

All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Aginode is indicative only and shall not be binding on Aginode or be treated as constituting a representation on the part of Aginode.

# AGINODE D-CORE 2x6 BA+RG LSZH Eca 500M

## Eigenschaften

### Konstruktionsmerkmale

|                |  |
|----------------|--|
| Schirm         | Aluminium-Polyester tape + tinned copper braid |
| Außenmantel    | LSZH   |
| Mantelfarbe    | Schwarz  |
| Aderfarbe      | Weiss - rot                                    |
| Leitermaterial | Bare copper class 5                            |
| Isolierung     | VPE  |

### Abmessungsmerkmale

|                                      |                   |
|--------------------------------------|-------------------|
| Nettogewicht ca.                     | 223 kg/km         |
| Aussendurchmesser                    | 12 mm             |
| Aderanzahl                           | 2                 |
| Leiterquerschnitt                    | 6 mm <sup>2</sup> |
| Durchmesser über Isolierung, Bereich | 4.8...5.0 mm      |

### Elektrische Eigenschaften

|  |            |
|--|------------|
| Max. Gleichstromwiderstand des Leiters bei 20° C | 3.3 Ohm/km |
| Minimaler Isolationswiderstand                   | 10 MOhm.km |
| Breakdown voltage Vcc, 5 min.                    | 3500.0 V   |

### Anwendungsmerkmale

|                               |                          |
|-------------------------------|--------------------------|
| Korrosivität der (Brand-)Gase | IEC 60754-1; IEC 60754-2 |
| Betriebstemperatur            | -40...90 °C              |
| Flammwidrig                   | IEC 60332-1              |
| Rauchdichte                   | EN/IEC 61034-2           |
| Verpackung                    | Trommel 500m             |
| Lagertemperatur, Bereich      | -40...50 °C              |
| Biegefaktor bei Verlegung     | 8 (xD)                   |
| Biegefaktor nach Verlegung    | 4 (xD)                   |

All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Aginode is indicative only and shall not be binding on Aginode or be treated as constituting a representation on the part of Aginode.

## Erklärung zur Leistung

AGINODE D-CORE 2x6 BA+RG LSZH Eca 500M pdf — 120.92 KB Herunterladen ↕

*All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Aginode is indicative only and shall not be binding on Aginode or be treated as constituting a representation on the part of Aginode.*