

AGINODE PTTA D-CORE - Eca

AGINODE D-CORE 2X16 BA+RG LSZH ECA 500M

Aginode Ref: 13200162

EAN: 3427630107843

Power To The Antenna D-CORE is a shielded dual conductor power cable. It can be used as a DC power cable for the interconnexion between Base Unit and Radio Units on mobile towers or rooftops. The D-shape of the isolated conductors enables to reduce the diameter and weight of these cables with no negative impact on the properties. It also has best-in-class flexibility.

Applications

- Power cable 0.6/1.0 kV
- For indoor/outdoor applications
- Used on mobile phone masts


Cable construction

1. **Bare conductor strand - Class 5**
2. **Insulation (IEC 60811-1)XLPE**
3. **Longitudinal ALU/PET tape**
4. **Tinned copper braid (Coverage US >65%)**
5. **Outer sheath: Eca**
HFFR - Black

Environment

Designed to reduce the environment impact, Aginode cables are compliant with RoHS 2011/65 Directive and European Reach 1907/2006/EC regulation.

D-CORE Picture



STANDARDS

IEC 60332-1

IEC 60502-1

All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Aginode is indicative only and shall not be binding on Aginode or be treated as constituting a representation on the part of Aginode.

AGINODE D-CORE 2x16 BA+RG LSZH Eca 500M

Eigenschaften

Konstruktionsmerkmale

Schirm	Aluminium-Polyester tape + tinned copper braid
Außenmantel	LSZH
Mantelfarbe	Schwarz
Aderfarbe	Weiss - rot
Leitermaterial	Bare copper class 5
Isolierung	VPE

Abmessungsmerkmale

Nettogewicht ca.	430 kg/km
Aussendurchmesser	14.5 mm
Aderanzahl	2
Leiterquerschnitt	16 mm ²
Durchmesser über Isolierung, Bereich	5.9...6.1 mm

Elektrische Eigenschaften

Max. Gleichstromwiderstand des Leiters bei 20° C	1.21 Ohm/km
Minimaler Isolationswiderstand	10 MOhm.km
Breakdown voltage Vcc, 5 min.	3500.0 V

Anwendungsmerkmale

Korrosivität der (Brand-)Gase	IEC 60754-1; IEC 60754-2
Betriebstemperatur	-40...90 °C
Flammwidrig	IEC 60332-1
Rauchdichte	EN/IEC 61034-2
Verpackung	Trommel 500m
Lagertemperatur, Bereich	-40...50 °C
Biegefaktor bei Verlegung	8 (xD)
Biegefaktor nach Verlegung	4 (xD)

All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Aginode is indicative only and shall not be binding on Aginode or be treated as constituting a representation on the part of Aginode.

Erklärung zur Leistung

AGINODE D-CORE 2x16 BA+RG LSZH Eca 500M pdf — 120.92 KB Herunterladen ⚡

All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Aginode is indicative only and shall not be binding on Aginode or be treated as constituting a representation on the part of Aginode.