
Outlets: @XS-FAST

OUTLETS: @XS-FAST

Aginode Ref: TBD

- Up to 2 SC/LC adapters
- Wall mounted, on flush box, on a DIN rail and on most of the electrical equipment mounting supports on the market
- No lid-opening to fix the outlet
- Ready-to-fix kit in option



Application

By default, it is designed for flush wall mounting. It can also be adapted for use with DIN rails and most standard electrical mounting systems available on the market by means of an optional adapter plate. The @XS-FAST can additionally serve as a DTIO, acting as the termination point of the operator's access network.

STANDARDS

Aginode specification

Functional characteristics

The OTO can be installed with a pre-connected drop cable entering from either side, the bottom, or the rear. It features a dedicated splicing area and fibre management zone, enabling cable-to-cable or cable-to-pigtails splicing.

All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Aginode is indicative only and shall not be binding on Aginode or be treated as constituting a representation on the part of Aginode.

Outlets: @XS-FAST

Eigenschaften

Konstruktionsmerkmale	
Farbe	White RAL 9010
Werkstoff	Thermoplastic
Abmessungsmerkmale	
Tiefe	18 mm
Höhe	80 mm
Maximale Anzahl von Adaptern	2
Anzahl Spleiße	2
Breite	80 m
Mechanische Eigenschaften	
IK-Bewertung	5
Anwendungsmerkmale	
Adapter	SC/LC
Feuerbeständig	UL 94 V0
Mindestbiegeradius bei statischem Einsatz	15 mm
Betriebstemperatur	-5...45 °C
Verpackung	Paper bag
UV Beständigkeit	Ja
Watertightness	IP 50

Notice @XS-OUTLET FAST.pdf pdf — 5.26 MB Herunterladen

All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Aginode is indicative only and shall not be binding on Aginode or be treated as constituting a representation on the part of Aginode.