

UPSKY™ preterminated cable singlemode & multimode

UPSKY™ PRETERMINATED CABLE 72 LC (48MM + 24SM) / 80M

Aginode Ref: 13200648

- Single-mode and multimode fibres in the same cable
- 24/48/72 fibres
- High mechanical resistance
- Supplied with UPSKY™ BOX L/XL connector block

Design

- Small diameter cable
- Dielectric and non-polarized
- UV-resistant
- Waterproof

Installation

- Indoor and outdoor
- LSZH-FR

Environmentally friendly

- Eco-designed
- PEP Eco Passport
- Available upon request



All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Aginode is indicative only and shall not be binding on Aginode or be treated as constituting a representation on the part of Aginode.

UPSKY™ preterminated cable 72 LC (48MM + 24SM) / 80m

Eigenschaften

Konstruktionsmerkmale

Farbe	Schwarz
Außenmantel	LSZH-FR
Leitungsaufbau	Multitube with strenght member
Fibre optic type	SM G657 A2 or OM3
Additional strength member	Glass yarn

Abmessungsmerkmale

Nettogewicht ca.	85 kg/km
Anzahl der optischen Fasern	72
Kabeldurchmesser	8.9 mm

Mechanische Eigenschaften

Mechanische Festigkeit gegen Schläge	5N.m
Querdruckwiderstand (EN 187 000)	100daN/cm kg/cm
Maximum Pulling Tension	200daN (80 daN) kN

Anwendungsmerkmale

Mindestbiegeradius bei statischem Einsatz	178 mm
Lagertemperatur, Bereich	-40...70 °C
Art der Installation	Indoor/Outdoor
Umgebungstemperatur, Bereich	0...40 °C
Betriebstemperatur bewegte Anwendung	-40...70 °C

All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Aginode is indicative only and shall not be binding on Aginode or be treated as constituting a representation on the part of Aginode.