

# UPSKY™ preterminated cable singlemode & multimode

UPSKY™ PRETERMINATED CABLE 72 LC (48MM + 24SM) / 50M

**Aginode Ref:** 13200649

- Single-mode and multimode fibres in the same cable
- 24/48/72 fibres
- High mechanical resistance
- Supplied with UPSKY™ BOX L/XL connector block

## Design

- Small diameter cable
- Dielectric and non-polarized
- UV-resistant
- Waterproof

## Installation

- Indoor and outdoor
- LSZH-FR

## Environmentally friendly

- Eco-designed
- PEP Eco Passport
- Available upon request



All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Aginode is indicative only and shall not be binding on Aginode or be treated as constituting a representation on the part of Aginode.

# UPSKY™ preterminated cable 72 LC (48MM + 24SM) / 50m

## Eigenschaften

### Konstruktionsmerkmale

Farbe	Schwarz
Außenmantel	LSZH-FR (Dca s2 do)
Leitungsaufbau	Multitube à porteur central
Fibre optic type	SM G657 A2 or OM3
Additional strength member	Glass yarn

### Abmessungsmerkmale

Nettogewicht ca.	85 kg/km
Anzahl der optischen Fasern	72
Kabeldurchmesser	8.9 mm

### Mechanische Eigenschaften

Mechanische Festigkeit gegen Schläge	5N.m
Querdruckwiderstand (EN 187 000)	100daN/cm kg/cm
Maximum Pulling Tension	200daN (80 daN) kN

### Anwendungsmerkmale

Lagertemperatur, Bereich	-40...70 °C
Art der Installation	Indoor/Outdoor
Umgebungstemperatur, Bereich	0...40 °C