
UPSKY™ preterminated cable singlemode & multimode

UPSKY™ PRETERMINATED CABLE 72 LC (48MM + 24SM) / 50M



Aginode Ref: 13200649

- Single-mode and multimode fibres in the same cable
- 24/48/72 fibres
- Hight mechanical resistance
- Supplied with UPSKY™ BOX L/XL connector block

Design

- Small diameter cable
- Dielectric and non-polarized
- UV-resistant
- Waterproof

Installation

- Indoor and outdoor
- LSZH-FR

Environmentally friendly

- Eco-designed
- PEP Eco Passport
- Available upon request

All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Aginode is indicative only and shall not be binding on Aginode or be treated as constituting a representation on the part of Aginode.

UPSKY™ preterminated cable 72 LC (48MM + 24SM) / 50m

Eigenschaften

Konstruktionsmerkmale	
Farbe	Schwarz
Außenmantel	LSZH-FR (Dca s2 do)
Leitungsaufbau	Multitube à porteur central
Fibre optic type	SM G657 A2 or OM3
Additional strength member	Glass yarn
Abmessungsmerkmale	
Nettogewicht ca.	85 kg/km
Anzahl der optischen Fasern	72
Kabeldurchmesser	8.9 mm
Mechanische Eigenschaften	
Mechanische Festigkeit gegen Schläge	5N.m
Querdruckwiderstand (EN 187 000)	100daN/cm kg/cm
Maximum Pulling Tension	200daN (80 daN) kN
Anwendungsmerkmale	
Lagertemperatur, Bereich	-40...70 °C
Art der Installation	Indoor/Outdoor
Umgebungstemperatur, Bereich	0...40 °C

All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Aginode is indicative only and shall not be binding on Aginode or be treated as constituting a representation on the part of Aginode.