

# LANmark-OF Loose Tube Universal 6-12 and 24FO - Dca

## LANMARK-OF LOOSE TUBE UNIVERSAL 12XMULTIMODE 50/125 OM3 LSZH DCA AQUA

### Aginode Ref: N165.LTUN12-AD

- Loose Tube Universal optical fibre cable with high level transmission : OM3
- Good fire behavior : reaction to fire Dca according to EN50575:2014+A1:2016
- Indoor / Outdoor cable
- Designed for splicing with pigtails


The new 12FO OM3 Loose Tube technology from Aginode is specifically engineered for both indoor and outdoor installations where high performance and fire safety are essential. Designed with a loose tube construction, it offers reliable protection for fibers against mechanical stresses and environmental factor.

- **CPR (Dca-s2, d1, a1):** Low fire propagation, reduced smoke emission, minimal toxic gas release.
- **Loose Tube Construction:** Excellent fiber protection against mechanical stress and temperature variations.
- **Indoor & Outdoor Applications:** Ideal for structured cabling in residential, commercial, and public buildings, as well as outdoor environments.
- **High Performance OM3 :** Reliable, high-speed data transmission over medium long distances.
- **Flexible and Robust:** Easy to install in ducts, conduits, and technical spaces.

The central tube contains till 12 fibers well identified to make installation easy and simple.

### Applications :

- Building backbone networks
- Data centers
- Outdoor installations



### STANDARDS

ISO/IEC 11801

# LANmark-OF Loose Tube Universal 12xMultimode 50/125 OM3 LSZH Dca Aqua

## Eigenschaften

### Konstruktionsmerkmale

Leitungsaufbau	Loose Tube
Fasertyp	OM3 50/125
Halogenfrei	IEC 60754-1
Verwendetes Material für Längswasserdichtigkeit	Swellable Glass yarns
Metallfrei	Yes
Tube Filling Compound Material	Thixotropic Gel

### Abmessungsmerkmale

Nettogewicht, ca	70 kg/km
Außendurchmesser, nom.	7.2 mm
Anzahl der optischen Fasern	12
Anzahl der Bündel	1
Rohrdurchmesser	3.8 mm

### Mechanische Eigenschaften

Crush resistance (IEC 60794-1-E3)	2000 N/100mm
Maximale Zugspannung bei Installation	2000 N
Maximalzulässige Dauerzuglast	0.7 kN
Max. Zugkraft (IEC 60794-1-2-E1)	2000 N
Mechanische Festigkeit gegen Schläge	10 impacts of 3 N.m

### Anwendungsmerkmale

flammwidrig	IEC 60332-3
Flammwidrig	IEC 60332-1-2
Umgebungstemperatur, Bereich	-30...60 °C
Dynamischer Mindestbiegeradius während Anwendung	152 mm
Mindestbiegeradius bei statischem Einsatz	114 mm
Betriebstemperatur	-40...70 °C

All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Aginode is indicative only and shall not be binding on Aginode or be treated as constituting a representation on the part of Aginode.

Rauchdichte	IEC 61034-2
Lagertemperatur, Bereich	-40...70 °C
UV Beständigkeit	Very good

## DoP: Declaration of Performance

DOP\_LANmark-OF Loose Tube Universal 12xMultimode 50/125 OM3 LSZH Dca Aqua.pdf pdf — 59.14 KB [Herunterladen](#) ↕