

LANmark-OF Loose Tube Universal 6-12 and 24FO - Dca

LANMARK-OF LOOSE TUBE UNIVERSAL 06XMULTIMODE 50/125 OM4 LSZH DCA VIOLET

Aginode Ref: N167.LTUN06-VD

- Loose Tube Universal optical fibre cable with high level transmission : OM4
- Good fire behavior : reaction to fire Dca according to EN50575:2014+A1:2016
- Indoor/Outdoor cable
- Designed for splicing with pigtails


The new 6FO OM4 Loose Tube technology from Aginode is specifically engineered for indoor and outdoor installations where both high performance and fire safety are essential. Designed with a loose tube construction, it offers good protection for fibers against mechanical stresses and environmental factors.

- **CPR (Dca-s2, d1, a1):** Low fire propagation, reduced smoke emission, minimal toxic gas release.
- **Loose Tube Construction:** Excellent fiber protection against mechanical stress and temperature variations.
- **Indoor & Outdoor Applications:** Ideal for structured cabling in residential, commercial, and public buildings, as well as outdoor environments.
- **High Performance OM4 :** Reliable, high-speed data transmission over medium long distances.
- **Flexible and Robust:** Easy to install in ducts, conduits, and technical spaces.

The central tube contains till 6 fibers well identified to make installation easy and simple.

Applications :

- Building backbone networks
- Data centers
- Outdoor installations



STANDARDS

ISO/IEC 11801

LANmark-OF Loose Tube Universal 06xMultimode 50/125 OM4 LSZH Dca Violet

Eigenschaften

Konstruktionsmerkmale

Leitungsaufbau	Loose Tube
Fasertyp	OM4 50/125
Halogenfrei	IEC 60754-1
Verwendetes Material für Längswasserdichtigkeit	Swellable Glass yarns
Tube Filling Compound Material	Thixotropic Gel

Abmessungsmerkmale

Nettogewicht, ca	56 kg/km
Außendurchmesser, nom.	6.2 mm
Anzahl der optischen Fasern	6
Anzahl der Bündel	1
Rohrdurchmesser	2.8 mm

Mechanische Eigenschaften

Crush resistance (IEC 60794-1-E3)	2000 N/100mm
Maximale Zugspannung bei Installation	2000 N
Maximalzulässige Dauerzuglast	0.7 kN
Max. Zugkraft (IEC 60794-1-2-E1)	2000 N
Mechanische Festigkeit gegen Schläge	10 impacts of 3 N.m

Anwendungsmerkmale

flammwidrig	IEC 60332-3
Flammwidrig	IEC 60332-1-2
Umgebungstemperatur, Bereich	-30...60 °C
Dynamischer Mindestbiegeradius während Anwendung	152 mm
Mindestbiegeradius bei statischem Einsatz	114 mm
Betriebstemperatur	-40...70 °C
Rauchdichte	IEC 61034-2

All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Aginode is indicative only and shall not be binding on Aginode or be treated as constituting a representation on the part of Aginode.

Lagertemperatur, Bereich

-40...70 °C

UV Beständigkeit

Very good

DoP: Declaration of Performance

DOP_LANmark-OF Loose Tube Universal 06xMultimode 50/125 OM4 LSZH Dca Violet.pdf pdf — 59.09 KB Herunterladen ↓