

LANmark-OF Loose Tube Universal 6 -12 and 24FO - Cca

LANMARK-OF LOOSE TUBE UNIVERSAL 12XMULTIMODE 50/125 OM4 LSZH CCA AQUA

Aginode Ref: N167.LTUN12-AC

- Loose Tube Universal optical fibre cable with high level transmission : OM4
- High fire behavior : reaction to fire Cca according to EN50575:2014+A1:2016
- Indoor/Outdoor cable
- Designed for splicing with pigtails

The new 12FO OM4 Loose Tube technology from Aginode is specifically engineered for indoor building & outdoor where installations where both high performance and fire safety are essential. Designed with a loose tube construction, it offers good protection for fibers against mechanical stresses and environmental factors.

- **CPR (Cca, s2, d1, a1) :** Low fire propagation, reduced smoke emission, minimal toxic gas release.
- **Loose Tube Gel-Filled Design:** Excellent protection against mechanical stress, water ingress, and temperature variations.
- **Vertical installations with loop reserve** for simplified maintenance and future upgrades.
- **Indoor & Outdoor Application:** Ideal for structured cabling in residential, commercial, and public buildings, as well as outdoor environments.
- **High Performance OM4 :** Reliable, high-speed data transmission over long distances.
- **Flexible and Robust:** Easy to install in ducts, conduits, and technical spaces.
- **UV-Resistant & Waterproof:** Designed to withstand outdoor conditions when required.

The central tube contains till 12 fibers well identified to make installation easy and simple.

Applications :

- Building backbone networks
- Data centers
- Outdoor duct installations



STANDARDS

ISO/IEC 11801

All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Aginode is indicative only and shall not be binding on Aginode or be treated as constituting a representation on the part of Aginode.

LANmark-OF Loose Tube Universal 12xMultimode 50/125 OM4 LSZH Cca Aqua

Eigenschaften

Konstruktionsmerkmale

Leitungsaufbau	Loose Tube
Fasertyp	OM4 50/125
Halogenfrei	IEC 60754-1
Jacket material	LSZH Halogen free flame retardant
Verwendetes Material für Längswasserdichtigkeit	Swellable Glass yarns

Abmessungsmerkmale

Nettogewicht ca.	71 kg/km
Außendurchmesser, nom.	7.6 mm
Anzahl der optischen Fasern	12
Anzahl der Bündel	1
Rohrdurchmesser	2.3 mm

Mechanische Eigenschaften

Crush resistance (IEC 60794-1-E3)	1500 N/100mm
Max. Zugkraft (IEC 60794-1-2-E1)	2000 N
Reißfestigkeit	2000 N

Anwendungsmerkmale

flammwidrig	IEC 60332-3
Flammwidrig	IEC 60332-1-2
Korrosivität der (Brand-)Gase	niedrig, gem. IEC 60754-2
Umgebungstemperatur, Bereich	-30...60 °C
Dynamischer Mindestbiegeradius während Anwendung	152 mm
Mindestbiegeradius bei statischem Einsatz	114 mm
Betriebstemperatur	-40...70 °C
Rauchdichte	IEC 61034-2
Lagertemperatur, Bereich	-40...70 °C
UV Beständigkeit	Very good

All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Aginode is indicative only and shall not be binding on Aginode or be treated as constituting a representation on the part of Aginode.