

LANmark-OF UC PE (Einrohr-Stahlarmierung)

LANMARK-OF UC 6X MULTIMODE 50/125 OM3 PE BLACK

Aginode Ref: N165.UCPE06B

UC optical fibre cables

- Outdoor in ducts or direct burial
- Corrugated steel tape armour
- Available in all fibres grades
- Provides full rodent protection


Description and Application

The construction is suitable for use outdoor in ducts and for direct burial. It consists of a corrugated steel tape armouring providing full rodent protection. It is surrounded by glass yarns. The cable has a HDPE outer jacket.

The loose tube design has a capacity of up to 24 fibres.

Diameter of the fibres is 255 µm. Termination of these fibres is done with splicing of pigtails.

The cable is watertight due to the gel in the loose tube and the watertight glass yarns.



STANDARDS

ISO/IEC 11801

LANmark-OF UC 6x Multimode 50/125 OM3 PE Black

Eigenschaften

Konstruktionsmerkmale

Leitungsaufbau	Loose Tube
Fasertyp	OM3 50/125
Halogenfrei	Ja
Jacket material	Polybutylene Terephthalate (PBT)
Verwendetes Material für Längswasserdichtigkeit	Swellable Glass yarns

Abmessungsmerkmale

Nettogewicht ca.	64 kg/km
Außendurchmesser, nom.	7.6 mm
Anzahl der optischen Fasern	6
Anzahl der Bündel	1
Rohrdurchmesser	2.8 mm

Mechanische Eigenschaften

Crush resistance (IEC 60794-1-E3)	2000 N/100mm
Reißfestigkeit	2000 N

Anwendungsmerkmale

Umgebungstemperatur, Bereich	-30...70 °C
Betriebstemperatur	-40...70 °C
Rauchdichte	IEC 61034-2
Lagertemperatur, Bereich	-40...70 °C
UV Beständigkeit	Very good

DoP : Declaration of Performance

DOP_UC 6xMM50 OM3 BK.pdf pdf — 58.99 KB [Herunterladen](#) ↓

All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Aginode is indicative only and shall not be binding on Aginode or be treated as constituting a representation on the part of Aginode.