DCmark Rack Unit Solution Server DC

DCMARK RACK UNIT SOLUTION SERVER DC 42U 600X1200



Aginode Ref: NRCK.420612330-B

The DCmark RUS NRCK.420612330-B is a high-performance server rack engineered for optimal airflow thanks to his high perforation ratio at 80%. With the need of IA and GPU server more and more heavy, the DCmark rack metallic frame is designed to support high loading capacity :

- Loading capacity up to 1500kg to support heavy server
- Perforation ratio at 80% to offer a perfect air flow
- Single door for a better access
- optional : rear support for intelligent PDU and internal lateral cable tray

The NRCK.42061233-B, offer a height of 42U with a depth of 1200mm and width of 600mm

The DCmark RUS NRCK.420612330-B is a high-performance server rack engineered for optimal airflow thanks to his high perforation ration at 80%. With the need of IA and GPU server more and more heavy, the DCmark rack metallic frame is designed to support high loading capacity up to 1500kg.

Equipped with several features, DCmark Rack Unit Solution will ensure reliability, easy installation & easy maintenance for DC technician.

The single front door will offer a full access to the cabling in order to facilitate all technical intevention inside the rack. The doors are equipped with a 3 locking points system closing to ensure high security level. Smart handle with RFDI card can be also installed to avoid key management (optional)

The NRCK.42061233-B, offer a height of 42U with a depth of 1200mm and width of 600mm

All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Aginode is indicative only and shall not be binding on Aginode or be treated as constituting a representation on the part of Aginode.

DCmark Rack Unit Solution Server DC 42U 600x1200

Eigenschaften

Konstruktionsmerkmale	
Schaltschrankformat	19"
Kabeleingang	From the top through brush panel and from bottom through sliding acess
Cabling management	Lateral front cable manager
Farbe	Schwarz
Werkstoff	Steel
Gehäuseversion	Server
Type of front door	double perforated at 80%
Type of rear door	double perforated at 80%
Abmessungsmerkmale	
19'' mounting	front & rear
Nettogewicht, ca.	121 kg
Tiefe	1200 mm
Höhe	2017 mm
Einheitshöhe	42 U
Breite	600 m
Mechanische Eigenschaften	
IK-Bewertung	07
Anwendungsmerkmale	
Locking system	3 locking points with mechanical handle
Verpackung	carton

All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Aginode is indicative only and shall not be binding on Aginode or be treated as constituting a representation on the part of Aginode.