

# Optical frames for TDCOP

## OPTICAL FRAME, 8 LEVELS

**Aginode Ref:** 10273748

Optical frame with pitch 400mm and 8 levels dedicated to optical cable head modules.

The optical frame is an ODF solution with an openframe structure dedicated for fixing of optical cable heads and suitable for high capacity Central Offices or POPs (It can reach up to 3.25m in height in 10-level configuration). Frame is built by assembling two aluminium profiles to which the following components are attached :

- jumpering rings
- fixing screws for cable heads with a pitch of 255mm

There are several frame models from 5 to 10 levels. The capacity of each level can reach 144 fibers (SC) with the optical cable head TDCOP 144OF.

The floor clearance of each frame is about 700mm. In order to build up the main distribution frame, each frame comes with a kit of parts with which the frames can be assembled at a pitch of 400 mm and subsequently be bolted to the floor.

A set accessories for cabling to be mounted after assembly is also supplied.


To protect the main distribution frame, front/rear and side protective strips are available in option.

**Sizes of optical frames**



### STANDARDS

Aginode specification



All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Aginode is indicative only and shall not be binding on Aginode or be treated as constituting a representation on the part of Aginode.

# Optical frame, 8 levels

## Eigenschaften

### Konstruktionsmerkmale

Werkstoff	Aluminium
-----------	-----------

### Abmessungsmerkmale

Tiefe	820 mm
-------	--------

Höhe	2500 mm
------	---------

Breite	400 mm
--------	--------

### Anwendungsmerkmale

Einsatzbereich	Innenraum
----------------	-----------

Mindestbiegeradius bei statischem Einsatz	30 mm
---	-------

Verpackung	Box
------------	-----

## Dokumentation

Installation manual - Optical frame pdf — 570.1 KB [Herunterladen](#) ↓