Coffrets muraux 19'' COF19



Coffrets 19’’ modulaire avec des panneaux latéraux amovibles ou une embase pivotante, un design sobre avec une conception robuste et une arrivée des câbles par le fond ou le toit par brosse avec plaque de fixation pour systèmes d'arrimage et d'épanouissement.

Les coffrets muraux 19" COF19 permettent d’accueillir tout équipement telecom au format 19’’ (modules optiques, actif, bandeaux de brassage RJ45 ⋯) et ainsi répondre à tout type d’installation réseaux.

Leur conception modulaire convient à une large gamme d’exigences :

- Largeur 600
- Profondeur 350+150 avec embase pivotante ou 400 avec panneaux latéraux amovibles
- Hauteur utile de 6U à 18U

Ils sont équipées de :

- Porte vitrée ouverture à gauche avec serrure (clefs fournies), montage à droite possible
- Embase pivotante ou panneaux latéraux amovibles avec serrure
- 2 montants 19’’ avant réglables en profondeur
- Plaque de fixation pour systèmes d'arrimage et d'épanouissement
- Fixation murale
- Passe-fils à brosse largeur 250mm en partie haute ou basse (si coffret retourné)
- Prédécoupes défonçables du coté opposé
- Inserts pour de mise à la terre

Fixation et ouverture des panneaux latéraux

STANDARDS

Aginode specification

All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Aginode is indicative only and shall not be binding on Aginode or be treated as constituting a representation on the part of Aginode.



All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Aginode is indicative only and shall not be binding on Aginode or be treated as constituting a representation on the part of Aginode.

Coffrets muraux 19'' COF19

CARACTÉRISTIQUES

Caractéristiques de construction	
Couleur	Gris clair RAL 7035
Matériau	Acier
Caractéristiques dimensionnelles	
Profondeur	400 mm
Hauteur (mm)	337 mm
Largeur	600 mm
Caractéristiques d'utilisation	
Application	Intérieur
Rayon de courbure minimum en utilisation statique	30 mm
Fermeture	Clé
Conditionnement	Carton
Etanchéité	IP 20

Information de livraison

Unitaire en carton

All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Aginode is indicative only and shall not be binding on Aginode or be treated as constituting a representation on the part of Aginode.

Product list

	Aginode ref.	Country ref.	Name	Hauteur (mm)
	10261227	-	Coffret mural 19'' COF19 standard 6U	337 (mm)
	10261228	-	Coffret mural 19'' COF19 standard 10U	515 (mm)
	10261229	-	Coffret mural 19'' COF19 standard 12U	604 (mm)
	10261230	-	Coffret mural 19'' COF19 standard 15U	737 (mm)
	10261231	-	Coffret mural 19'' COF19 standard 18U	871 (mm)
	10261232	-	Coffret mural 19'' COF19 pivotant 6U	337 (mm)
	10261233	-	Coffret mural 19'' COF19 pivotant 10U	515 (mm)
	10261344	-	Coffret mural 19'' COF19 pivotant 12U	604 (mm)
	10261345	-	Coffret mural 19'' COF19 pivotant 15U	737 (mm)
	10261346	-	Coffret mural 19'' COF19 pivotant 18U	871 (mm)

= Make to order, = In Stock

All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Aginode is indicative only and shall not be binding on Aginode or be treated as constituting a representation on the part of Aginode.