

LANmark-OF UG Indoor/Outdoor PE 2-24C APAC Region

- Indoor / Outdoor in ducts
- Glass yarns protection and HDPE jacket
- Available up to 24 fibers
- Watertight and rodent protection
- Bending Insensitive Fibers for OM3,OM4 cables

Application

The construction is suitable for use indoor and outdoor in ducts.

It is surrounded by glass yarns and providing rodent protection.

The cable has a HDPE outer jacket.

The loose tube design has a capacity of up to 24 fibers.

Diameter of the fibres


is 250 um. Termination of these fibres is done with splicing of pigtails.

The cable is watertight due to the gel in the loose tube and the watertight glass yarns.

Construction

Legend accompanying the cross section drawing:

1. Optical fibres (250um)
2. Gel
3. Loose tube
4. Reinforced watertight glass yarns
5. HDPE outer jacket



STANDARDS

ANSI/TIA-568-C.3

IEC 60793-2-10

ISO/IEC 11801

LANmark-OF UG Indoor/Outdoor PE 2-24C APAC Region

CARACTÉRISTIQUES

Caractéristiques de construction

Type de fibres optiques	OM3 50/125
-------------------------	------------

Caractéristiques dimensionnelles

Diamètre extérieur	7.2 mm
--------------------	--------

Masse	43 g
-------	------

Nombre de fibres optiques	4
---------------------------	---

Caractéristiques mécaniques

Résistance mécanique aux chocs (IEC 60794-1-E4)	100 impacts of 1 N.m
---	----------------------

Crush resistance (IEC 60794-1-E3)	2000 N/100mm
-----------------------------------	--------------

Maximum pulling force (IEC 60794-1-2-E1)	1700 N
--	--------

Caractéristiques d'utilisation

Température ambiante d'utilisation, plage	-20...60 °C
---	-------------

Rayon de courbure minimum en utilisation dynamique	144.0 mm
--	----------

Rayon de courbure minimum en utilisation statique	72 mm
---	-------

Température de stockage, plage	-20...70 °C
--------------------------------	-------------

Température ambiante d'installation, plage	0...40 °C
--	-----------

Product list

	Aginode ref.	Country ref.	Name
☎	N175.841	-	LANmark-OF UG 4 x Multimode 50/125 BI OM3 PE Black
☎	N175.842	-	LANmark-OF UG 6 x Multimode 50/125 BI OM3 PE Black
☎	N175.843	-	LANmark-OF UG 8 x Multimode 50/125 BI OM3 PE Black
☎	N175.845	-	LANmark-OF UG 12 x Multimode 50/125 BI OM3 PE Black
☎	N175.851	-	LANmark-OF UG 24 x Multimode 50/125 BI OM3 PE Black
☎	N177.840	-	LANmark-OF UG 2 x Multimode 50/125 BI OM4 PE Black
☎	N177.841	-	LANmark-OF UG 4 x Multimode 50/125 BI OM4 PE Black
☎	N177.842	-	LANmark-OF UG 6 x Multimode 50/125 BI OM4 PE Black
☎	N177.843	-	LANmark-OF UG 8 x Multimode 50/125 BI OM4 PE Black
☎	N177.845	-	LANmark-OF UG 12 x Multimode 50/125 BI OM4 PE Black
☎	N177.851	-	LANmark-OF UG 24 x Multimode 50/125 BI OM4 PE Black
☎	N174.840	-	LANmark-OF UG 2 x Singlemode 9/125 G.652.D PE Black
☎	N174.841	-	LANmark-OF UG 4 x Singlemode 9/125 G.652.D PE Black
☎	N174.842	-	LANmark-OF UG 6 x Singlemode 9/125 G.652.D PE Black
☎	N174.843	-	LANmark-OF UG 8 x Singlemode 9/125 G.652.D PE Black
☎	N174.845	-	LANmark-OF UG 12 x Singlemode 9/125 G.652.D PE Black
☎	N174.851	-	LANmark-OF UG 24 x Singlemode 9/125 G.652.D PE Black
☎	N175.840	-	LANmark-OF UG 2 x Multimode 50/125 BI OM3 PE Black

☎ = Make to order, 🏠 = In Stock

All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Aginode is indicative only and shall not be binding on Aginode or be treated as constituting a representation on the part of Aginode.