

LANmark-OF Bow fibre cable 1-2C

- Most suitable for floor routing
- Smaller bending radius fiber
- Easy core take out with notch structure
- Fire retardant IEC 60332-1 & IEC60332-3C

Characteristics

Special low-bend-sensitivity fiber provides high bandwidth and excellent communication transmission property.

Singlemode G657A2 performance: compliant to IEC60793-2-10, subtype B6a.2

Novel flute design ,easily strip and splice ,simplify the installation maintenance.

Construction

Legend accompanying the cross section drawing:

1. Optical fibre
2. FRP
3. Outer sheath in LSZH material



STANDARDS

ANSI/TIA-568-C.3

IEC 60793-2-10

ISO/IEC 11801

LANmark-OF Bow fibre cable 1-2C

CARACTÉRISTIQUES

Caractéristiques de construction

Couleur	Noir
Type de fibres optiques	SM (G657.A2)

Caractéristiques dimensionnelles

Hauteur (mm)	2 mm
Masse	8 g
Largeur	3 mm
Nombre de fibres optiques	2

Caractéristiques mécaniques

Résistance mécanique aux chocs (IEC 60794-1-E4)	100 impacts of 1 N.m
Crush resistance (IEC 60794-1-E3)	1000 N/100mm
Maximum pulling force (IEC 60794-1-2-E1)	80 N

Caractéristiques de transmission

Affaiblissement nominal à 1310 nm	0.5 dB/1000m
Affaiblissement maximal à 1550 nm	0.4 dB/1000m

Caractéristiques d'utilisation

Température ambiante d'utilisation, plage	-20...60 °C
Rayon de courbure minimum en utilisation statique	15 mm
Température de stockage, plage	-20...60 °C

Product list

	Aginode ref.	Country ref.	Name
☎	N174CH.002	-	FTTH Bow-type Drop Cable 2F LSZH,BLACK
☎	N174CH.001	-	FTTH Bow-type Drop Cable 1F LSZH,BLACK

☎ = Make to order, 📦 = In Stock

All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Aginode is indicative only and shall not be binding on Aginode or be treated as constituting a representation on the part of Aginode.