Câble à fibres optiques LANmark-OF Bow 1-2C

- Idéal pour le pose au sol
- Fibre à rayon de courbure réduit
- Retrait facile du cœur grâce à la structure crantée
- Ignifuge selon les normes CEI 60332-1 et CEI 60332-3C



Caractéristiques

Une fibre spéciale à faible sensibilité à la flexion offre une bande passante élevée et d'excellentes propriétés de transmission des signaux.

Performances de la fibre monomode G657A2 : conforme à la norme CEI 60793-2-10, sous-type B6a.2

Conception innovante des cannelures, facilitant le dénudage et l'épissure, ce qui simplifie l'installation et la maintenance.

Construction

Légende accompagnant le schéma en coupe transversale :

1. Fibre optique
2. FRP
3. Gaine extérieure en matériau LSZH

STANDARDS

ANSI/TIA-568-C.3
IEC 60793-2-10
ISO/IEC 11801

All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Aginode is indicative only and shall not be binding on Aginode or be treated as constituting a representation on the part of Aginode.

Câble à fibres optiques LANmark-OF Bow 1-2C

CARACTÉRISTIQUES

Caractéristiques de construction	
Type de fibres optiques	SM (G657.A2)
Couleur	Noir
Caractéristiques dimensionnelles	
Largeur	3 mm
Masse	8 g
Hauteur (mm)	2 mm
Caractéristiques mécaniques	
Résistance mécanique aux chocs (IEC 60794-1-E4)	100 impacts of 1 N.m
Maximum pulling force (IEC 60794-1-2-E1)	80 N
Crush resistance (IEC 60794-1-E3)	1000 N/100mm
Caractéristiques de transmission	
Affaiblissement nominal à 1310 nm	0.5 dB/1000m
Affaiblissement maximal à 1550 nm	0.4 dB/1000m
Caractéristiques d'utilisation	
Température de stockage, plage	-20...60 °C
Température ambiante d'utilisation, plage	-20...60 °C
Rayon de courbure minimum en utilisation statique	15 mm

All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Aginode is indicative only and shall not be binding on Aginode or be treated as constituting a representation on the part of Aginode.

Product list

	Aginode ref.	Country ref.	Name
	N174CH.002	-	Câble de dérivation FTTH de type « Bow » 2F LSZH, NOIR
	N174CH.001	-	Câble de dérivation FTTH de type « Bow » 1F LSZH, NOIR
	N174CH.004	-	Câble de dérivation FTTH de type « Bow » 4F LSZH, NOIR

= Make to order, = In Stock

All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Aginode is indicative only and shall not be binding on Aginode or be treated as constituting a representation on the part of Aginode.