

U-GUARD - Compact duct and aerial cable Max span 50m

This cable is specially designed to be installed by pulling in occupied ducts.

It is also a very good candidate for jetting installation types.


On top of this it can be installed aerial for short spans up to 50m.

Characteristics & Applications

- Compact in size
- Excellent installation performances due to the excellent friction properties of the outer sheath
- Central strength member reinforcement
- High pulling strength
- All dielectric design
- Waterproof dry core structure
- Rodent Repellent (RR) Outersheath
- Compatible with helical dead-ends

Construction

- Jelly filled tubes containing coloured fibres
- Central FRP strength member
- Very Low friction outer sheath
- Strong HDPE outer jacket with 1mm wall thickness
- Rodent Repellent outer sheath



STANDARDS

EN 187000
IEC 60794

U-GUARD - Compact duct and aerial cable Max span 50m

CARACTÉRISTIQUES

Caractéristiques de construction

Type de construction	Libre
Type de fibres optiques	SM (G657.A1)
Gaine extérieure	PE haute densité
Porteur central	Central FRP

Caractéristiques dimensionnelles

Nombre de fibres optiques	72
Nombre de tubes	6

Caractéristiques d'utilisation

Température ambiante lors de l'installation, plage	-10...50 °C
Rayon de courbure en cours de pose	20 (xD)
Type d'installation	Duct - Air jetting or pulling - Aerial short span 50m
Température ambiante d'utilisation, plage	-30...70 °C
Protection Anti-Rongeurs	Anti rodent additive
Température de stockage, plage	-40...70 °C

Information de livraison

Standard Marking

Aginode - MF - SPxxxx - FIBRE OPTIC CABLE - XX*YY - TN - metric

XX = Fibre Count

YY = Fibre Type

TN = Traceability Number

All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Aginode is indicative only and shall not be binding on Aginode or be treated as constituting a representation on the part of Aginode.

Product list

Aginode ref.	Country ref.	Name	Armure	Type de fibres optiques	Nombre de fibres optiques	Nombre de tubes
☎ 14500780	Greece	U-GUARD LT COMPACT LOOSE TUBE CABLE 6X12SM SP2053	Non armé	SM (G657.A1)	72	6
☎ 14500567	Greece	U-GUARD LT COMPACT LOOSE TUBE CABLE 8X12SM SP2054	Non armé	SM (G657.A1)	96	8
☎ 14500568	Greece	U-GUARD LT COMPACT LOOSE TUBE CABLE 12X12SM SP2055	Non armé	SM (G657.A1)	144	12
☎ 14500569	Greece	U-GUARD LT COMPACT LOOSE TUBE CABLE 24X12SM SP2056	Non armé	SM (G657.A1)	288	24

☎ = Make to order, 📦 = In Stock