

Transition adapters

FIBREROUTE 240MM(9.45 INCH)-120MM(4.75 INCH) UNEQUAL CROSS COVER

Aginode Ref: N350.240FT71A

Aginode Fibre Trunking propose un système de cheminement pour câbles et cordons fibre optique afin de les protéger des dommages accidentels. Ce système offre une solution flexible et haute capacité pour les centres de données, simple à installer et reconfigurer pour s'adapter aux besoins futurs.

- Pathway system designed for accommodation of data centre fibre cables
- Free of sharp edges
- Quick connect system with a wide range of fixtures and fittings
- High capacity pathway accommodating large volumes of cables with space for future expansion
- Unequal cross to create symmetrical 120mm(4.75 inch) branches from 240mm(9.45 inch) main channels
- ABS material

The Aginode Fibre Trunking System provides a dedicated pathway through data centre spaces and IT facilities for routing fibre cables.

The rigid channel with matching cover protects fibre optic cables from damage.

All components of the system are made of tough, fire retardant materials.

The system components have a smooth inner surface to ensure a safe path for fibre optic cables and feature internal radius management to facilitate the maintenance of bend radii for cables and patch cords.

The Trumpet is used to provide an exit from 120mm(4.75 inch) channels whilst maintaining fibre bend radii.

All components of the system including the covers can be installed and uninstalled without special tools.

All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Aginode is indicative only and shall not be binding on Aginode or be treated as constituting a representation on the part of Aginode.



STANDARDS

EN 50173-5
ISO/IEC 24764
UL 94 V0

FIBREROUTE 240mm(9.45 inch)-120mm(4.75 inch) Unequal Cross Cover

Caractéristiques

Caractéristiques de construction

Couleur	Jaune
Matériau	ABS

Caractéristiques dimensionnelles

Masse nette approximative	0.3 kg
---------------------------	--------

Caractéristiques d'utilisation

Température ambiante d'utilisation, plage	-25...60 °C
Température de stockage, plage	-45...60 °C