

# essential-OF TB LSZH 2-24C - APAC Region

## ESSENTIAL-OF TIGHT BUFFER LSZH SM G.652.D 24C YELLOW

**Aginode Ref:** N274.TBIN24Y

Tight buffered optical fibre cables

- Indoor cable designed for backbone/horizontal installation
- Available in OM3 and SingleMode G.652.D
- Outer Jacket is Low Smoke Zero Halogene (LSZH)

### Description and Application

Essential-OF TB Indoor fibre cable is designed for indoor applications especially for building. The fibre cable has 900µm tight buffered fibres. The cable is coated with aramid yarns, and the outer jacket is LSZH with good fire performance. Essential-OF TB is available for Bend Insensitive OM3 and SingleMode G.652.D.


The fibre cable is of a dry structure suitable for horizontal or vertical installation. The fibre cable meets the needs of indoor fire protection and can be installed in ducts.

- Can be installed both vertically or horizontally
- Applicable as standard multimode and singlemode fibre
- LSZH Jacket
- Tight buffered fibre

### Construction

Legend accompanying the cross section drawing for 2-24core OF cable:

1. 900µm Tight buffered fibre
2. Aramid yarn
3. LSZH jacket materials



### STANDARDS

ANSI/TIA-568-C.3  
IEC 60332-1  
IEC 60332-3-24 Cat.C  
IEC 60793-2-10  
ISO/IEC 11801

# Essential-OF Tight Buffer LSZH SM G.652.D 24C YELLOW

## Caractéristiques

### Caractéristiques de construction

Couleur	Jaune
Type de fibres optiques	SM (G.652D)

### Caractéristiques dimensionnelles

Diamètre extérieur	8 mm
Nombre de fibres optiques	24

### Caractéristiques mécaniques

Résistance mécanique aux chocs (IEC 60794-1-E4)	100 impacts of 1 N.m
Crush resistance (IEC 60794-1-E3)	1000 N/100mm
Maximum pulling force (IEC 60794-1-2-E1)	660 N

### Caractéristiques d'utilisation

Température ambiante d'utilisation, plage	-20...60 °C
Rayon de courbure minimum en utilisation dynamique	160.0 mm
Rayon de courbure minimum en utilisation statique	80 mm
Température de stockage, plage	-20...60 °C
Température ambiante d'installation, plage	0...40 °C