
LANmark-6A UTP Cable

LANMARK-6A UTP AWG24 CAT 6A LSZH CCA S1A D1 A1 ORANGE 500M REEL



Aginode Ref: N100.638GD-B3L

- Fully compliant with Category 6A standards
- Support 10GBase-T applications
- Guaranteed performance to 500MHz
- Noise immunity tape for enhanced Alien Crosstalk performance
- Reaction-to-fire performance according to CPR classification Cca-s1a,d1,a1 (h/EN50575:2014+A1:2016)

Application

LANmark-6A cables have been specifically designed to support the higher frequencies required for 10 Gigabit Ethernet, whilst maintaining full backwards compatibility with lower speed applications.

They are manufactured and tested to the latest Category 6A specifications of the European, international and American cable standards and meet the quality and performance criteria needed to support all applications up to 500 MHz.

- 10Base-T Ethernet
- 100Base-TX Fast Ethernet
- 1000Base-TX Gigabit Ethernet
- 10GBase-T 10 Gigabit Ethernet
- 155 Mbit ATM
- 1.2 Gbit ATM
- future Cat 6A and Class EA applications

Design

Aginode LANmark-6A UTP cables feature a double-sided plasticized alu tape which ensures the stringent internal and Alien Crosstalk requirements for Category 6A are met whilst requiring no earthing or bonding.

The cables have a central cross element which maintains the stability of the cable geometry and reduces the risk of decreased performance when bending the cable.

They feature an Orange LSZH sheath and are available in both EuroClass Dca and Cca compliant versions according to EN50575:2014+A1:2016.

STANDARDS

ANSI/TIA 568.2-D
EN 50173-1
EN 50288
IEC 61156-5
IEEE 802.3bt (PoE++)
ISO/IEC 11801

All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Aginode is indicative only and shall not be binding on Aginode or be treated as constituting a representation on the part of Aginode.

Performance

With guaranteed performance to 500MHz, Aginode LANmark-6A UTP cables meet the requirements of the International, European and American cable standards for Category 6A as specified in IEC 61156-5, EN 50288 and TIA/EIA 568.2-D.

Systems built with LANmark-6A UTP cable and connectors, in conjunction with LANmark-10G patch cords, support 10GBase-T applications as defined in IEEE 802.3an and meet the link and channel requirements for Category 6A and Class EA as specified in TIA/EIA 568.2-D and ISO/IEC 11801 including all alien crosstalk related parameters.

Installation

LANmark-6A UTP cable allows swift and rapid installation as no earthing or bonding is required.

To support the correct set-up of hand held analysers for installation testing, the actual cable NVP value is given in the cable print legend.

Guarantees

Traceability codes on both cable and packaging ensure quality validation of the installed cable.

Installations with LANmark-6A UTP cable and connectivity qualify for a 25 year Class EA Channel warranty when used in combination with LANmark patch cords.

Electrical Performance LANmark-6A UTP Cable

Freq in MHz	Attn in dB Max.	NEXT in dB Min.	PSNEXT in dB Min.	ACR-F in dB Min.	PS ACR-F in dB Min.	TCL in dB Min.	ELTCTL in dB Min.	PS ANEXT in dB Min.	PS AACR-F in dB Min.	RL in dB Min.
1	2,1	75,0	72,3	67,8	64,8	40,0	35,0	67,0	67,0	20,0
4	3,8	66,3	63,3	55,8	52,8	40,0	23,0	67,0	66,2	23,0
10	5,9	60,3	57,3	47,8	44,8	40,0	15,0	67,0	58,2	25,0
16	7,5	57,2	54,2	43,7	40,7	38,0	10,9	67,0	54,1	25,0
20	8,4	55,8	52,8	41,8	38,8	39,0	NA	67,0	52,2	25,0
31,25	10,5	52,9	49,9	37,9	34,9	35,1	NA	67,0	48,3	23,6
62,5	15,0	48,4	45,4	31,9	28,9	32,0	NA	65,6	42,3	21,5
100	19,1	45,3	42,3	27,8	24,8	30,0	NA	62,5	38,2	20,1
155	24,1	42,0	39,4	24,0	21,0	28,5	NA	59,6	34,4	18,8
200	27,6	40,8	37,8	21,8	18,8	27,0	NA	58,0	32,2	18,0
250	31,1	39,3	36,3	19,8	16,8	26,0	NA	56,5	30,2	17,3
300	34,3	38,1	35,1	18,3	15,3	25,2	NA	55,3	28,7	17,3
500	45,3	34,8	31,8	13,8	10,8	23,0	NA	52,0	24,2	17,3

All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Aginode is indicative only and shall not be binding on Aginode or be treated as constituting a representation on the part of Aginode.

LANmark-6A UTP AWG24 Cat 6A LSZH Cca s1a d1 a1 Orange 500m reel

Caractéristiques

Caractéristiques de construction	
Couleur	Bleu
Gaine extérieure	PVC
Type de câble	UTP
Caractéristiques dimensionnelles	
Section AWG du conducteur	AWG 23
Diamètre sur isolation	1.12 mm
Diamètre externe nominal (mm)	7.4 mm
Caractéristiques électriques	
Capacité effective	56 nF/km
Impédance caractéristique	100 Ohm
Résistance ohmique max. du conducteur à 20°C	85 Ohm/km
Caractéristiques mécaniques	
Maximum operating pulling force	100 N
Caractéristiques de transmission	
Distorsion	45 ns/100m
Retard de propagation maximal à 100 MHz	536 ns/100m
Caractéristiques d'utilisation	
Gamme	LANmark-6A
Longueur	305 m
Température ambiante d'utilisation, plage	-20...60 °C
Catégorie	Cat. 6A
Non propagateur de la flamme	CMR - UL 1666
Conditionnement	Reel
Température ambiante lors de l'installation, plage	0...50 °C
Minimum Bend Radius - During Installation (under Tension)	59.2 mm
Rayon de courbure minimum - installé	29.6 mm

All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Aginode is indicative only and shall not be binding on Aginode or be treated as constituting a representation on the part of Aginode.