LANmark-OF MUN (Module Universel) - Cca

LANMARK-OF MODULE UNIVERSAL 48FO OS2 - CCA

Aginode Ref: N164.MUN48-YC

- Micro-Bundle Universal optical fibre cable
- Indoor cable and outdoor installation in a duct
- Fully waterproof and rodent resistant
- LSZH sheath, CPR **Cca** fire-rated for enhanced safety
- Small, but mechancial strong cable
- Designed for splicing with pigtails
- Micro-bundles of 12fibres



ISO/IEC 11801

The LANmark-OF MUN (Module Universal) cable is designed for **indoor and outdoor** installations, compatible with duct installation. It is optimized for both horizontal and vertical indoor applications thanks to its strict fire performance rating.

Key features :

All-dielectric design, eliminating any conductive materials.

Jelly-filled micro-modules, each containing 12 fibres, offering excellent fibre protection and easy identification.

Available in all standard fibre grades (e.g., OS2, OM3, OM4).

Waterproof structure with dry water-swellable glass yarns for optimal water blocking.

Rodent resistance and UV resistance, ensuring high durability in outdoor environments.

Flame retardant according to IEC 60332-1 and fire retardant according to IEC 60332-3, meeting strict indoor safety requirements.

Compliant with gas toxicity (IEC 60754) and smoke density (IEC 61034) standards, rated Euroclass **Cca-s1,d1,a1** for fire safety.

All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Aginode is indicative only and shall not be binding on Aginode or be treated as constituting a representation on the part of Aginode.

LANmark-OF Module Universal 48FO OS2 - Cca

Caractéristiques

Caractéristiques de construction	
Type de construction	Multibundle
Type de fibres optiques	SM (G657.A1)
Sans halogène	Oui
Matière constituant l'étanchéité longitudinale	Swellable Glass yarns
Gaine extérieure	Faible dégagement de fumée et sans halogène
Caractéristiques dimensionnelles	
Masse approximative	85 kg/km
Diamètre du câble	10 mm
Nombre de fibres optiques	48
Caractéristiques mécaniques	
Crush resistance (IEC 60794-1-E3)	1000 N/100mm
Dynamic bending raidus	15xcable OD
Tension maximale à l’installation	2700 N
Résistance mécanique aux chocs (IEC 60794-1-E4)	10 impacts of 1 N.m
Static Bending radius	10xcable OD
Caractéristiques d'utilisation	
Non propagateur de la flamme	IEC 60332-1
Température ambiante d'installation, plage	-5...40 °C
Type d'installation	Intérieur / Extérieur
Température ambiante d'utilisation, plage	-25...70 °C
Densité de fumée dégagée	IEC 61034-2
Température de stockage, plage	-40...70 °C
Tenue aux UV	Très bonne

All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Aginode is indicative only and shall not be binding on Aginode or be treated as constituting a representation on the part of Aginode.