

LANmark-OF DB Outdoor PE 2-144core APAC Region

LANMARK-OF OUTDOOR DB OPTICAL FIBER CABLE,SINGLEMODE G.652.D 9/125 12F,PE,BLACK, APAC REGION

Aginode Ref: N174.12DBPE

- Suitable for outdoor application in ducts or direct burial
- Robust structure with water-blocking material
- Fiber available in OM3/OM4/G.652.D/G.657.A1, up to 144 cores
- Double steel tape armoring provides full rodent protection
- Loose tube with gel


DESCRIPTION

DB outdoor cable is suitable for outdoor application in ducts or direct burial. The cable is watertight due to the gel in the loose tube and water-blocking material in cable. It consists of double corrugated steel tape armoring providing full rodent protection. The cable outer jacket is PE, UV-resistant and good weatherability. Diameter of the fibers is 250 um. Termination of fibers can be done with splicing of pigtailed.

Construction

Legend accompanying the cross section drawing:

1. Optical fibers (250um)
2. Tube filling compound
3. Loose tube
4. APL
5. Water-blocking gel
6. PE outer jacket
7. PSP
8. PE inner jacket
9. Filler
10. Central strength member
11. Water-blocking gel



STANDARDS

ANSI/TIA-568.3-D
IEC 60794
ISO 11801 Ed.3

LANmark-OF Outdoor DB optical fiber cable, Singlemode G.652.D 9/125 12F, PE, Black, APAC Region

Caractéristiques

Caractéristiques de construction

Armure	Double Metal Tape
Gaine extérieure	PE
Couleur de la gaine	Noir

Caractéristiques mécaniques

Résistance à l'écrasement (IEC 794-1-E3)	300 N/cm
Maximum pulling force (IEC 60794-1-2-E1)	3000 N
Résistance mécanique aux chocs (IEC 60794-1-E4)	10 impacts of 10 N.m

Caractéristiques d'utilisation

Température ambiante lors de l'installation, plage	0...40 °C
Rayon de courbure minimum en utilisation dynamique	166 mm
Rayon de courbure minimum en utilisation statique	332 mm
Température ambiante d'utilisation, plage	-40...70 °C
Température de stockage, plage	-40...70 °C