

# essential-OF Fixed Patch Panels SP(Selected Package) Version

**ESSENTIAL-OF 1U 24-PORT PATCH PANEL,12 DUPLEX LC ADAPTERS AND 24 G652D SM PIGTAILS,WITH MOUNTING AND SPLICING ACCESSORIES,BLACK**

## **Aginode Ref: N441.4SPL24**

- 1U Fixed Patch Panels with standard adaptors for wide compatibility
- Up to 24 simplex SC or duplex LC adapters
- Ready to use configuration, equipped with 12 duplex LC adapters and 24 G652D SM pigtails
- Delivered with all accessories like splicing set and mounting screw set.
- The rear end latch is convenient for removing the upper cover plate
- White silkscreen label above each ports
- Suitable for 19-inch cabinets and racks installation

essential-OF fixed patch panel SP(Selected Package) Version from Aginode, which is simple and easy to operate resulting in better customer experience. Typical installation conditions for the Aginode' essential-OF Fixed Patch Panel are backbones for offices, campus, and small data centers, while providing the required density, it also provides simplicity and flexibility.

The patch panel designed with duplex LC or simplex SC standard adaptors, and delivered with pigtails and accessories. SP(Selected Package) Version covered the most popular configuration for quick deployment on site. please refer to detailed characteristics.

Multiple cables can be fixed in the rear of the tray with tie wraps, and there are 4 slots with a diameter of 20mm at the rear end.

The Fixed Patch Panels suitable for 19-inch cabinets and racks installation, the surface is fully painted black frosted ink jet.



## **STANDARDS**

ANSI/TIA-568.3-D  
ISO/IEC 11801

# essential-OF 1U 24-port patch panel,12 duplex LC adapters and 24 G652D SM pigtails,with mounting and splicing accessories,black

## Caractéristiques

### Caractéristiques de construction

|                         |            |
|-------------------------|------------|
| Fibre Type Connector    | LC/UPC     |
| Type de fibres optiques | SM (G.652) |

### Caractéristiques dimensionnelles

|                  |           |
|------------------|-----------|
| Largeur          | 19 inches |
| Profondeur       | 235 mm    |
| Unité de hauteur | 1 U       |

### Caractéristiques d'utilisation

|         |                   |
|---------|-------------------|
| Raccord | Duplex LC SM Blue |
|---------|-------------------|