

Transition adapters

FIBREROUTE 600MM(23.62 INCH)-360MM(14.17 INCH) REDUCER

Aginode Ref: N350.600FT04A

Aginode Fiber Trunking System provides a dedicated pathway for fiber optic cables and cords to protect them from accidental damage. The system offers a flexible, high-capacity solution for data center containment which is easy to install and reconfigure to meet future needs.

- Pathway system designed for accommodation of data center fiber cables
- Free of sharp edges
- Quick connect system with a wide range of fixtures and fittings
- High capacity pathway accommodating large volumes of cables with space for future expansion
- Reducer allows the interconnection of 600mm(23.62 inch) and 360mm(14.17 inch) systems
- Tough, flame retardant ABS material

The Aginode Fiber Trunking System provides a dedicated pathway through data center spaces and IT facilities for routing fiber cables.

The rigid channel with matching cover protects fiber optic cables from damage.

All components of the system are made of tough, fire retardant materials.

The system components have a smooth inner surface to ensure a safe path for fiber optic cables and feature internal radius management to facilitate the maintenance of bend radii for cables and patch cords.

All components of the system including the covers can be installed and uninstalled without special tools.



STANDARDS

EN 50173-5
ISO/IEC 24764
UL 94 V0

FIBREROUTE 600mm(23.62 inch)-360mm(14.17 inch)

Reducer

Caractéristiques

Caractéristiques de construction

Matériau	ABS
Couleur	Jaune

Caractéristiques dimensionnelles

Profondeur	118 mm
------------	--------

Caractéristiques d'utilisation

Température de stockage, plage	-45...60 °C
Température ambiante d'utilisation, plage	-25...60 °C