Supporting Kits

FIBREROUTE 600MM(23.62 INCH) MOUNTING BOTTOM BAR KIT



Aginode Ref: N350.003SMB5

Aginode Fibre Trunking System provides a dedicated pathway for fibre optic cables and cords to protect them from accidental damage. The system offers a flexible, high-capacity solution for data centre containment which is easy to install and reconfigure to meet future needs.

- Mounting kits available for various data centre installation environments
- Supporting Bar for Trapeze/hanging style mounting, can be use when the thread rod is already installed on site.

600mm(23.62 inch) Mounting Bottom Bar Kit includes crosspiece and screws.

N350.003SMB5 is available for 600mm(23.62") series. Distance between center of mounting holes on the crosspiece is 550mm(21.65"). Total length of the crosspiece is 600mm(23.62").

STANDARDS

EN 50173-5
ISO/IEC 24764

All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Aginode is indicative only and shall not be binding on Aginode or be treated as constituting a representation on the part of Aginode.

FIBREROUTE 600mm(23.62 inch) Mounting Bottom Bar Kit

Caractéristiques

Caractéristiques de construction	
Couleur	Metalic
Matériau	Acier
Caractéristiques dimensionnelles	
Masse nette approximative	2.2 kg
Caractéristiques d'utilisation	
Température ambiante d'utilisation, plage	-25...60 °C
Température de stockage, plage	-45...60 °C

All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Aginode is indicative only and shall not be binding on Aginode or be treated as constituting a representation on the part of Aginode.