OPTEASTAR 2+ 19'' cabinet base 800x300



Cabinet 800x300 height 42 or 45U with full rigth door or with window and locking system with key or triangle (8mm).

OpteaStar 2+ cabinets can be located on different interconnection nodes on fiber optic network (WAN, SAN, LAN or FTTx) for configurations point to point or PON with integration of splitters in Central Office or POP (Point Of Presence), or even for riser mutualization at the basement of a building with a large number of subscribers.

To answer to this plurality of solutions, its design is based on an optimized modularity allowing high density connectivity for all types of cabling :

- Inter-frame patching
- Interconnection
- Cross-connection

OpteaStar 2+ cabinets are compatible with all types of 19''optical modules (except subrack). Depending on the need, the range is available in various heights up to 2200mm, a standard depth of 300 mm and a width of 600, 900 or optimized to 800mm.

This OpteaStar 2+ version also facilitates the assembly of several cabinets (side by side or back to back) for big sites and allows an openrack use. This is very easy to disassemble the cabinet, a delivery in kit is possible on demand in case of difficult access (staircase).

STANDARDS

Aginode specification

Composition

Single OpteaStar 2+ cabinets consist in a mechano-screwed structure composed with :

- 2 up and down welded frames size 800x300
- 4 profiles for corners
- A roof with brushes and full baseplate interchangeable
- A fixing plate for clamping or fanout systems
- A bottom plate allowing management of tubes and cables behind the optical modules with rings (provided)
- A coiling area for patchcords overlengths with drums

All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Aginode is indicative only and shall not be binding on Aginode or be treated as constituting a representation on the part of Aginode.

- 2 removable side panels
- A rear panel
- 2 asymmetrical doors
- 4 adjustable feet
- A grounding point
- A wall fixing kit

This composition will be adapted depending on the configuration.


Cabling

Fiber optic cables entry is performed by the plinth or by the roof. Cables clamping and fanout is also made in lower or upper part on each cabinet.

Fixing


Cabinet can be fixed to the wall, the floor, back to back or side by side.

800x300 cabinet configurations



Cable management behind the modules

All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Aginode is indicative only and shall not be binding on Aginode or be treated as constituting a representation on the part of Aginode.



W coiling principle

##image:92558:center##

Only one length of patchcord for all configurations of patching.

All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Aginode is indicative only and shall not be binding on Aginode or be treated as constituting a representation on the part of Aginode.

OPTEASTAR 2+ 19'' cabinet base 800x300

CHARACTERISTICS

Construction characteristics	
Colour	Grey
Material	Steel
Dimensional characteristics	
Depth	300 mm
Width	800 mm
Heightunit	42 U
Mechanical characteristics	
IK Rating	10
Usage characteristics	
Operating temperature, range	-10...60 °C
Minimum static operating bending radius	30 mm
Locking system	Triangle
Packaging	Pallet
Installation type	Indoor
Watertightness	IP 20
Rodent resistant	Optional

Resources

ドキュメンテーション

Installation manual - OPTEASTAR 2+ single cabinets pdf — 3.33 MB　ダウンロード

販売および配送情報

Packaging : 2 cabinets per pallet 800x1200

All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Aginode is indicative only and shall not be binding on Aginode or be treated as constituting a representation on the part of Aginode.

Product list

	Aginode ref.	Country ref.	名前	Heightunit	Locking system	Watertightness
	10268018	-	Cabinet 42U with full doors, 19'' rack to left, top entry & locking with triangle	42 (U)	Triangle	IP 20
	10268019	-	Cabinet 42U with full doors, 19'' rack to left, bottom entry & locking with triangle	42 (U)	Triangle	IP 21
	10268020	-	Cabinet 42U with full doors, 19'' rack to left, top entry & locking with key	42 (U)	Key	IP 20
	10268021	-	Cabinet 42U with full doors, 19'' rack to left, bottom entry & locking with key	42 (U)	Key	IP 21
	10268022	-	Cabinet 42U with glass door, 19'' rack to left, top entry & locking with triangle	42 (U)	Triangle	IP 20
	10268023	-	Cabinet 42U with glass door, 19'' rack to left, bottom entry & locking with triangle	42 (U)	Triangle	IP 21
	10268034	-	Cabinet 42U with glass door, 19'' rack to left, top entry & locking with key	42 (U)	Key	IP 20
	10268035	-	Cabinet 42U with glass door, 19'' rack to left, bottom entry & locking with key	42 (U)	Key	IP 21
	10268036	-	Cabinet 45U with full doors, 19'' rack to left, top entry & locking with triangle	45 (U)	Triangle	IP 20
	10268037	-	Cabinet 45U with full doors, 19'' rack to left, bottom entry & locking with triangle	45 (U)	Triangle	IP 21
	10268038	-	Cabinet 45U with full doors, 19'' rack to left, top entry & locking with key	45 (U)	Key	IP 20
	10268039	-	Cabinet 45U with full doors, 19'' rack to left, bottom entry & locking with key	45 (U)	Key	IP 21
	10268040	-	Cabinet 45U with glass door, 19'' rack to left, top entry & locking with triangle	45 (U)	Triangle	IP 20
	10268041	-	Cabinet 45U with glass door, 19'' rack to left, bottom entry & locking with triangle	45 (U)	Triangle	IP 21
	10268042	-	Cabinet 45U with glass door, 19'' rack to left, top entry & locking with key	45 (U)	Key	IP 20
	10268043	-	Cabinet 45U with glass door, 19'' rack to left, bottom entry & locking with key	45 (U)	Key	IP 21
	10268044	-	Cabinet 42U with full doors, 19'' rack to right, top entry & locking with triangle	42 (U)	Triangle	IP 20
	10268045	-	Cabinet 42U with full doors, 19'' rack to right, bottom entry & locking with triangle	42 (U)	Triangle	IP 21
	10268046	-	Cabinet 42U with full doors, 19'' rack to right, top entry & locking with key	42 (U)	Key	IP 20

All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Aginode is indicative only and shall not be binding on Aginode or be treated as constituting a representation on the part of Aginode.

	Aginode ref.	Country ref.	名前	Heightunit	Locking system	Watertightness
	10268047	-	Cabinet 42U with full doors, 19'' rack to right, bottom entry & locking with key	42 (U)	Key	IP 21
	10268048	-	Cabinet 42U with glass door, 19'' rack to right, top entry & locking with triangle	42 (U)	Triangle	IP 20
	10268049	-	Cabinet 42U with glass door, 19'' rack to right, bottom entry & locking with triangle	42 (U)	Triangle	IP 21
	10268050	-	Cabinet 42U with glass door, 19'' rack to right, top entry & locking with key	42 (U)	Key	IP 20
	10268051	-	Cabinet 42U with glass door, 19'' rack to right, bottom entry & locking with key	42 (U)	Key	IP 21
	10268052	-	Cabinet 45U with full doors, 19'' rack to right, top entry & locking with triangle	45 (U)	Triangle	IP 20
	10268053	-	Cabinet 45U with full doors, 19'' rack to right, bottom entry & locking with triangle	45 (U)	Triangle	IP 21
	10268054	-	Cabinet 45U with full doors, 19'' rack to right, top entry & locking with key	45 (U)	Key	IP 20
	10268055	-	Cabinet 45U with full doors, 19'' rack to right, bottom entry & locking with key	45 (U)	Key	IP 21
	10268056	-	Cabinet 45U with glass door, 19'' rack to right, top entry & locking with triangle	45 (U)	Triangle	IP 20
	10268057	-	Cabinet 45U with glass door, 19'' rack to right, bottom entry & locking with triangle	45 (U)	Triangle	IP 21
	10268058	-	Cabinet 45U with glass door, 19'' rack to right, top entry & locking with key	45 (U)	Key	IP 20
	10268059	-	Cabinet 45U with glass door, 19'' rack to right, bottom entry & locking with key	45 (U)	Key	IP 21

= Make to order, = In Stock

All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Aginode is indicative only and shall not be binding on Aginode or be treated as constituting a representation on the part of Aginode.