アウトドロップ 2+

- ベアファイバー管理用SFMオーガナイザーとスプライストレー
- マイクロバンドルおよびルースチューブケーブルとの互換性
- ケーブルの収納タンク・ブロック・エレメント（アンチ・ピストニング）
- 見た目のインパクトが少ない堅牢な製品
- 最大16個のSCアダプターを接続可能
- すべてのバージョンにスプリッターを統合



OUTDROPボックスは加入者ケーブルの空中展開用に設計されています。また、1/4回転ボタンで固定することもできます。空中ボックスに
マイクロバンドルやルースケーブルに対応したオーガナイザートレイには、ケーブルを固定するためのアンカーエリアと、ファイバーの重

ファイバー管理

ファイバーはスパイスカセットで管理されます。カセットは連結式で、スプライスに素早く簡単にアクセスできます。
このボックスは、異なるバージョンのカセットやオーガナイザーを使用でき、最大72個のスプライスを収容できます。すべてのカセットに
SFMオーガナイザーとカセットを使用すると、接続中のファイバー、輸送中のファイバー、保留中のファイバーを区別してベアファイバー
パッチ・バージョンでは、24個のスプライスと16個のSCアダプタに制限されています。

ケーブル構成

本製品は、2つのラテラル・ポート（オプション）により、ミッドスパン・ケーブル（バットまたはストレート・ミッドスパン）の使用に
ラバーシール付きポートは、外部使用での保護等級（IP55）を保証します。最大直径14mmまでのケーブルと、最大直径6mmまでのドロ



STANDARDS

Aginode specification

All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Aginode is indicative only and shall not be binding on Aginode or be treated as constituting a representation on the part of Aginode.

アウトドロップ 2+

CHARACTERISTICS

Construction characteristics	
Colour	Light grey RAL 7035
Material	Polycarbonate
Dimensional characteristics	
Height	78 mm
Width	236 mm
Length	247 mm
Max. number of cassettes	2
Splice number	72
Number of branched cables	12
Diameter main cable	4...14 mm
Diameter branch cable	4...6 mm
Mechanical characteristics	
IK Rating	9
Usage characteristics	
Operating temperature, range	-40...65 °C
Midspan	Yes
Minimum static operating bending radius	15 mm
U.V resistance	Yes
Packaging	Box
Installation type	Aerial Cable
RoHS compliant	Yes
Watertightness	IP 55

Resources

ドキュメンテーション

OUTDROP splicing 72OF for G657A2 fibre - instructions (FR/EN) pdf — 1.77 MB　ダウンロード

OUTDROP splicing 72OF SFM - instructions (FR/EN) pdf — 2.12 MB　ダウンロード

OUTDROP splicing 48OF - instructions (FR/EN) pdf — 1.55 MB　ダウンロード

All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Aginode is indicative only and shall not be binding on Aginode or be treated as constituting a representation on the part of Aginode.

OUTDROP patching - Version with plastic organiser - instructions (FR/EN) pdf — 1.34 MB　ダウンロード

All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Aginode is indicative only and shall not be binding on Aginode or be treated as constituting a representation on the part of Aginode.

Product list

	Aginode ref.	Country ref.	名前	Max. number of cassettes	Maximum number of adaptators	Splice number	Minimum static operating bending radius
	10268776	-	OUTDROP 2+ 72 OF for G657A2 fibre, horizontal and protected by 1/4 turn	2		72	15 (mm)
	10268733	-	OUTDROP 2+ 24 OF 水平、1/4回転で保護	2	12	24	30 (mm)
	10268774	-	OUTDROP 2+ 48 OF 水平、1/4回転で保護	4		48	30 (mm)
	10268778	-	OUTDROP 2+ SFM 36 OF 1/4回転で保護	3		36	30 (mm)
	10268777	-	OUTDROP 2+ SFM 72 OF 1/4回転で保護	6		72	30 (mm)
	10268779	-	OUTDROP 2+ 12 OF 12SC/APC、水平、1/4回転でプロテクト	1	12	12	30 (mm)
	10268780	-	OUTDROP 2+ 24 OF 12SC/APC、水平、1/4回転で保護	2	12	24	30 (mm)
	10273312	-	OUTDROP 2+が16SC/APCをパッチングし、1/4回転で固定。	1	16	30	30 (mm)

= Make to order, = In Stock

All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Aginode is indicative only and shall not be binding on Aginode or be treated as constituting a representation on the part of Aginode.